WATER WELL REPORT STATE OF OREGON

RECEIVED State Well No. FEB 29 1984

03545
PLEASE TYPE or PHYATER RESOURCES DEPT. SALEM, OREGON

1) OWNER:	(10) LOCATION OF WELL:	
Name IMF MINISTRY DEVELOPMENT	County CLACKAMAS Driller's well	number
Address 15035 SE 114 SUITE 201	NW 4NF 4 Section 29 T.25	R. 1
City CLACKAMAS State OR	Tax Lot # Lot Blk	Subdivision
2) TYPE OF WORK (check):	Address at well location: SO. Boklax	UD RD
New Well Deepening Reconditioning Abandon Abandon abandon I describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
	Depth at which water was first found 480	ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		and surface. Date 0 18 83
Rotary Air Driven Domestic LIndustrial Municipal D		r square inch. Date
Rotary Mud Dug Irrigation Test Well Other	(12) WELL LOG: Diameter of well below	enging R
		completed well 550 ft.
(5) CASING INSTALLED: Steel Plastic Dark Threaded Welded Dark	Formation: Describe color, texture, grain size and stru	
8. "Diam from +1 ft. to 427 ft. Gauge .ZSO	thickness and nature of each stratum and aquifer penet	trated, with at least one entry
	for each change of formation. Report each change in p and indicate principal water-bearing strata.	osition of Static water Level
LINER INSTALLED:	MATERIAL	From To SWL
"Diam fromft. toft. Gauge	BROWN CLAY	1 37
(6) PERFORATIONS: Perforated? ☐ Yes	CEMENTED GRAVEL W/	37 62
Type of perforator used	LARGE ROCKS	
Size of perforations in. by in.	BLUE CLAY	
perforations from ft. to ft.	GRAY CLAY	150 368
perforations from ft. to ft.,	GRAY-BLACK CLAY W/	368 375
perforations from ft. to ft.	DECOMPOSED ROCK	375 427
(7) SCREENS: Well screen installed? Yes 12-No	BASALT SOFT VERY FRAGULED	3/3 721
Manufacturer's Name	BASALT HARD GRAY W/	427 552 145
Type	SOME BROWN LAYERS	721 332 143
Diam. Slot Size Set from ft. to ft.	BASALT VERY LOOSE AND BROKEU	550 562 145
Diam. Slot Size Set from ft. to ft.	DRONEL	550 562 145
Drawdown is amount water level is lowered	1	
(8) WELL TESTS: below static level		
a pump test made? Yes I No If yes, by whom?	 	
gal./min. with ft. drawdown after hrs.		
11 и и и		
Air test 30+ gal./min. with drill stem at 370 ft. hrs.	•	
Bailer test gal/min. with ft. drawdown after hrs.		
sian flow g.p.m.		
Depth artesian flow encountered ft.	Work started 10 3 1983 Complete	ed 10/18 1983
(9) CONSTRUCTION: Special standards: Yes No	Date well drilling machine moved off of well	10/18 1963
Well seal—Material used LEMENT	(unbonded) Water Well Constructor Certifi	• •
Well sealed from land surface to	_	= =
Diameter of well bore to bottom of seal	This well was constructed under my direct s and information reported above are true to my b	
Diameter of well bore below seal	[Signed]	
Number of sacks of cement used in well seal		······································
How was cement grout placed?	Bonded Water Well Constructor Certificati	
now was centent group placed:	Bond 22/65/69 Issued by: Ohio	ety Company Name
	This well was drilled under my jurisdiction	and this report is true to
Was pump installed?	the best of my knowledge and belief.	
Was a drive shoe used? If Yes □ No Plugs	NameD V W (Person, firm or corporation)	(Type or print)
Did any strata contain unusable water?	Address 16150 SE NORMA RO MIL	
Type of Water? depth of strata		
Method of sealing strata off	[Signed] Water Well Construc	tor
Was well gravel packed? ☐ Yes 1140 Size of gravel:		1983
Gravel placed from ft to ft	A. W.	