NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

,		/
State	Well No.	25/1E-31

State	Well No. 25/1E-31
C4-4-	Down M. No.

(1) OWNER:	CHECATION OF WELL:
Name Stafford Baptist Church	County Clackamas Driller's well number
Address	1/4 1/4 Section 2/1 T. 12 R. W.M.
Wilsonville, Oregon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Bound and and and an acceptant of Barbary Short Collect
New Well [Deepening Abandon [Abandon [
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Rotary A Driven D Domestic A Industrial Municipal D	Depth at which water was first found 240 tft. Static level 190 tft. below land surface. Data 3/29/77
Canic Li Petreti	
org Bored Irrigation Test Well Other	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Dismeter of well below costno.
ft. Gage	Diameter of well below casing
"Diam. fromft. toft. Gage	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Ves No	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	
0 p	MATERIAL From To SWL
Size of perforations in. by in.	
perforations from	scoriacious
perforations from ft. to ft.	Basalt, black &
perforations fromft. toft.	brown, scoriacious 254 268 Basalt, black,
(7) SCREENS: Well screen installed? Yes No	scoriacious 268 279
Manufacturer's Name	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
The second secon	The second secon
// // // // // // // // // // // // //	The state of the s
Bailer test 15 gal./min. with 60 ft. drawdown after 1 hrs.	
Artesian flow g.p.m.	and the same of th
perature of water Depth artesian flow encounteredft.	Work started 3/29 19 77 Completed 3/29 1977
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3/29 1977
	Drilling Machine Operator's Certification:
Well seal—Material usedft.	This well was constructed under my direct supervision
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	
Number of sacks of cement used in well sealsacks	[Signed] Date 2/29, 19.77
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No1096
Brand name of bentonite	Weter Will Control of Control
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name D.V. Wyland & Co. Tro
Did any strata contain unusable water? 🛚 Yes 🖺 No	Name D. V. Wyland & Co. Inc. (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 734 8th Street, Lake Oswego, Or
Method of sealing strata off	[Signed] Lawel U. U. Contractor)
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 554 Date 3/29 , 1977
	EETS IF NECESSADV)