NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARMING FIVE DSTATE OF OREGON SALEM, OREGON 9730 FIVE D (Please type or print) within 30 days from the date of well completion.

ALCO C 1077 (Do not write above this line)

(Do not write above this line)

7140	ell No.	25/1E.	3100
-	State Permit 1	No	·

Mear 0 1977			
(1) OWNER: WATTE RESCURCES DEPT.	(10) LOCATION OF WELL:		
Name Ben Fritchie CALEM. ORECON	County Clackamas Driller's well number		
Address 22727 Stafford Road	SERW 14 NE 14 Section 31 T. 2S R. 1E W.M.		
Tualatin, Oregon 97062	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well □ Deepening KK Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 167 ft.		
Rotary 💆 Driven 🗌 Domestic 💆 Industrial 🗎 Municipal 🗍	Static level 158 ft. below land surface. Date 8/17/7		
Cable ☐ Jetted ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	Artesian pressure lbs. per square inch. Date		
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing6.		
"Diam. from	Depth drilled 237 ft. Depth of completed well 237 ft.		
" Diam. from ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
(b) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.			
perforations fromft. toft.	Basalt, red, black,		
perforations fromft. toft.	fractured, water 167 219 158		
perforations fromft. toft.	Basalt, red, very		
to the control of the	<u>fractured</u> 219 226 158		
(7) SCREENS: Well screen installed? Yes No	Basalt, black W/white		
Manufacturer's Name	mineral 226 237 158		
Type Model No.			
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	<u>*************************************</u>		
Diam. Stot size Set from			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			
d: gal./min. with ft. drawdown after hrs.			
" " "			
" " "			
Bailer test 12 gal./min. with 70 ft. drawdown after 1 hrs.			
	Work started 8/16 1977 Completed 8/17 1977		
perature of water Depth artesian flow encountered ft.			
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8/17 19 77		
Well seal—Material used	Drilling Machine Orierator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal	[Signed] Dut (Drilling Machine Operator)		
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 1096		
How was cement grout placed?	<u> </u>		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name D.V. Wyland & Co. Inc.		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 734 8th st. Ak Oswego, Or 97034		
Method of sealing strata off	[Signed] () and U () (
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)		
Gravel placed fromft. toft.	Contractor's License No. 554 Date 8/24 , 19.77		