

The original and first copy of this report are to be filed with the

RECEIVED JUL 27 1972

WATER WELL REPORT

STATE OF OREGON

CLAC

State Well No. 25/1E-33 da

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

STATE ENGINEER SALEM OREGON

(Type or print) (Do not write above this line) 03803

State Permit No.

(1) OWNER:

Name: STANLEY JEWETT
Address: R#1 BOX 339 WEST LANE, ORE 97068

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 79 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? [] Yes [X] No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Bailer test 28 gal./min. with 5 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT GROUT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 9 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [] Yes [X] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County CLACK. Driller's well number 5410
NE 1/4 SE 1/4 Section 33 T. 25 R. 1E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 98 ft.
Static level 72 ft. below land surface. Date 7/19/72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 132 ft. Depth of completed well 132 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: BROWN CLAY AND Boulders, GRAVEL, Boulders, GREY BASALT, BROKEN GREY BASALT, GREY BASALT.

Work started JULY 17 1972 Completed JULY 20 1972
Date well drilling machine moved off of well JULY 20 1972

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Dennis Schmidt Date JULY 24, 1972
(Drilling Machine Operator)
Drilling Machine Operator's License No. 564

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name R.L. SROSSER DRILLING Co
(Address, firm or corporation) (Type or print)
Address 810 SE SUNSET LAKE PORTLAND ORE
[Signed] Robert L. Srosser
(Water Well Contractor)
Contractor's License No. 10 Date JULY 24, 1972