The original and first by of this report are the second se	NC REPORTULAC
filed with the JUL 19/1 STATE OF OREGON State Well No. 2/2-2 bd	
STATE ENGINEER, SALEMOTH WE'RE NGINEER Please type within 30 days from the date LEM. OF CONDO not write at	bove this line) (5593 State Permit No.
	(0100)
(1) OWNER:	(10) LOCATION OF WELL:
Name GLENN SAUAGE Address P#1 Box 331, CLACKAMAS ORE.	County CLACK Driller's well number 527%
Address K#1 BOX 331, CLACKAMAS ORE.	NW14 SE 14 Section 2 T. 25 R. 2E W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1
Rotary Driven	Depth at which water was first found 348 ft.
Cable Jetted Domestic Industrial Municipal	Static level 2/3 ft. below land surface. Date 7/2/71
Dug Bored Irrigation 1 Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded M. C. Threaded	(12) WELL LOG: Diameter of well below casing
July Diam. from 330 ft. to 373 ft. Gage 377	
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	
	MATERIAL From To SWL
2./3	SEE ATTACHED SHEET
perforations from	
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ★ Yes □ No	
Manufacturer's Name UOP JOHNSON	
Type STAINLESS STEE Wodel No.	
Diam. Slot size 15 Set from 373 ft. to 388 ft.	
Diam. Slot size Set from ft. toft.	
(0) TITELY MERCING	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes \(\subseteq No \) If yes, by whom? \(\subseteq \textit{TRASSER} \)	
Yield: 165 gal./min. with 37 ft. drawdown after / hrs.	
225 " 58 " 2 "	
300 " 86 " 8 "	
Doilon took	
Ambanian Ci-	
Artesian flow g.p.m.	
Temperature of water 54 Depth artesian flow encountered ft.	Work started JUNE 2 1971 Completed JULY 7 1971
CONSTRUCTION:	Date well drilling machine moved off of well July 8 197
Well seal—Material used CEMENT GROUT	Drilling Machine Operator's Certification:
Well sealed from land surface to 30 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and helief
Diameter of well bore below seal	
Number of sacks of cement used in well sealsacks	[Signed] (Drilling Machine Operator) Date 5047/4, 1971
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No/75
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? X Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes X No	Name (Person, firm or corporation) (Type-or print)
Type of water? depth of strata	Address 8/10 SE SUNSET LANE FORTLAND ORG
Method of sealing strata off	Control li
Was well gravel packed? XYes ☐ No Size of gravel: 14-18	[Signed]
	(Water Well Contractor)
	Contractor's License No. 10 Date JULY 14, 1971
(USE ADDITIONAL SHEETS IF NECESSARY)	

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane
Portland, Oregon 97206

July 15, 1077

Log of 10 inch well for Rhododendron Nurseries

ST TE ENGINEER