The original and first copy of this report are to be filed with the STATE OF OREGON

STATE ENGINEER, SALEM, OR TATE ENGINEER type or print) within 30 days from the date of well completion. SALEM. OR I Workt write above this line)

CLAC
State Well No. 2/2-2dc

0394 Arte Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name MILWAUKIE HIGH SCHOOL	County CLACKAMAS Driller's well number 155
Address 2202 S.E. WILLARD	SE 4SW 4 Section 2 T. 2S R. 2E W.M.
MILWAUKIE OREGON	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well   Deepening □ Reconditioning □ Abandon □ .	e e e e e e e e e e e e e e e e e e e
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 225 ft.
Rotary D Driven D Domestic Industrial Municipal	Static level 194 /2 ft. below land surface. Date 6-23-7
Cable	Artesian pressure lbs. per square inch. Date
	The second pressure men second
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
" Diam. fromft. toft. Gage	Depth drilled 290 ft. Depth of completed well 290 ft.
4/2" Diam. from 259 ft. to 290 ft. Gage 188"	Formation: Describe color, texture, grain size and structure of materials;
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
***************************************	
Size of perforations (6 in. by in.	Benum CIA-
130 perforations from 260 ft. to 290 ft.	
perforations from ft. to ft.	GRAY BASALT 44 129
perforations from ft. to ft.	7 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
(7) SCREENS: Well screen installed?   Yes No	LOOSE GRAVEL 160 166
Manufacturer's Name	CEMENTED GRAVEL 166 173
Type Model No.	BROWN CLAY 173 183
Diam. Slot size Set from ft. to ft.	CEMENTED GRAVEL 183 198
Diam ft. to ft.	CLAY AND BOULDERS 198 203
	BLUE CLAY 203 221
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	SANDY BROWN CLAY 221 225
Was a pump test made? Yes No If yes, by whom? KELLER	BROWN SAND 225 229 186
Yield: 52 gal./min. with 48 ft. drawdown after 4 hrs.	CEMENTED GRAVEL 229 233
" " "	CLAY, SOME GRAVEL 233 237
" " " "	COMENTED CORAVEL 237247
Bailer test 40 gal./min. with 2.5 ft. drawdown after / hrs.	BLUE CLAY 247 356
	CLA-1, SAND AND GRAVEL 256 274
Artesian flow g.p.m.	SAND, CLAY, SOME GRAVEU 2/4 1290 1941
nperature of water — Depth artesian flow encountered ft.	Work started 3 - 2 / 19 // Completed 6 / 2 3 19 /
(9) CONSTRUCTION:	Date well drilling machine moved off of well 19
Well seal—Material used DENTONITE	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Date 6-28, 197/
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 329
Number of sacks of bentonite used in well seal sacks	Dinning Machine Operator's Interior 110.
Brand name of bentonite NATIONAL	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes □ No  Type of water? SANOY depth of strata 225'-229'	Address 5365 S.E. HILLWOOD MILWAUKIE
	EVO VOID
Method of sealing strata off CASING  Was well gravel packed? N Yes I No. Size of gravel: 4 MINUS	[Signed] (Water Well Contractor)
	to a compare the man of the contract of the co
Gravel placed from 259 ft. to 290 ft.	Contractor's License No. 404 Date, 19