

WATER WELL REPORT

STATE OF OREGON

COPY

RECEIVED  
CLAC  
003974 1987

State Well No. 15/3E-1

State Permit No.

PLEASE TYPE or PRINT IN INK  
WATER RESOURCES DEPT.  
SALEM OREGON

(1) OWNER:

Name Hoodview S.D.A. School  
Address 14385 SE 268<sup>th</sup> Ct.  
City Boring State Or.

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Air  Driven  Domestic  Industrial  Municipal   
 Mud  Dug  Irrigation  Test Well  Other   
 Casing  Bored  Thermal:  Withdrawal  ReInjection

(4) PROPOSED USE (check):

School water supply

(5) CASING INSTALLED:

Steel  Plastic   
Threaded  Welded   
8" Diam. from 0 ft. to 300 ft. Gauge 280

LINER INSTALLED:

" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Perforated?  Yes  No  
Type of perforator used Mills knife  
Size of perforations in by in.  
5 per ft. 3/16 perforations from 250 ft. to 296 ft.

(7) SCREENS:

Well screen installed?  Yes  No  
Manufacturer's Name  
Type Model No.  
Diam. Slot Size Set from ft. to ft.  
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level  
a pump test made?  Yes  No If yes, by whom? driller  
Yield: 102 gal./min. with 35 ft. drawdown after 5 hrs.  
Air test gal./min. with drill stem at ft. hrs.  
Boiler test 40 gal./min. with 10 ft. drawdown after 1 hrs.  
Artesian flow g.p.m.  
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes  No   
Well seal—Material used Cement grout  
Well sealed from land surface to below 180 ft.  
Diameter of well bore to bottom of seal in.  
Diameter of well bore below seal in.  
Number of sacks of cement used in well seal sacks  
How was cement grout placed?  
Was pump installed? Type HP Depth ft.  
Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of Water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clatsop Driller's well number  
1/4 Section 1 T. 15 R. 3E W.M.  
Tax Lot # Lot Blk Subdivision

Address at well location:

same

(11) WATER LEVEL: Completed well.

Depth at which water was first found  
Static level 225' ft. below land surface. Date Feb 1987  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing to bottom  
Depth drilled 355 ft. Depth of completed well 300 ft.  
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Red clay	1	18	
boulder clay	18	75	
sandy clay silt	75	170	
sand stone	170	222	
blue & brown clay	222	233	
dry cement gravel	233	250	
water bearing cement gravel	250	296	
blue clay	296	350	
blue sand water bearing	350	355	

Work started 19 Completed Feb 29 1987  
Date well drilling machine moved off of well 19

(unbonded) Water Well Constructor Certification (if applicable):  
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] Date, 19

Bonded Water Well Constructor Certification:  
Bond Issued by: Surety Company Name  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name A. O. Olson  
Address 35838 SE Wildcat Mt. Dr., Eagle Creek, Or. 97022  
[Signed] A. O. Olson Water Well Constructor Date 19

NOTICE TO WATER WELL CONSTRUCTOR  
The original of this report is on file at the