

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED WATER WELL REPORT

RECEIVED

Ja

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

DEC 27 1973 STATE OF OREGON
(Please type or print)

SEP 5 1973

State Well No. 25/2E-11

STATE ENGINEER
SALEM, OREGON
(Do not write above this line)

STATE ENGINEER
SALEM, OREGON
State Permit No. CLAC 04040

(1) OWNER:

Name River Bend Mobile Home Park
Address 13900 S.E. Hwy 212, Clackamas, Ore.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
8" Diam. from 0 ft. to 252 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
" " " " " "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:


County Clackamas Driller's well number
N.E. 1/4 S.E. 1/4 Section 11 T. 2S R. 2E W.M.
Bearing and distance from section or subdivision corner
160' S. & 570' from the N.E. Corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled ft. Depth of completed well ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
<u>Milia sand leak @250 ft.</u>			
<u>Was cemented, but didn't shut off the sand leakage.</u>			
<u>Have put an internal packer on pipe then telescoped into the bottom of 8" pipe. Ran the casing to top of well.</u>			
			
<u>Remaining To wait was Drilled 10-18-72 - 3-15-73</u>			

Work started 8-7 19 73 Completed 8-20 19 73
Date well drilling machine moved off of well 8-29 19 73

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Walter Mace Date 9-3, 19 73
(Drilling Machine Operator)
Drilling Machine Operator's License No. 595

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name S.M. Drilling & Supply Inc.
(Person, firm or corporation) (Type or print)
Address 399 S.E. Walnut Canby, Ore.
[Signed] Walter Mace
(Water Well Contractor)
Contractor's License No. 497 Date 9-3, 19 73