AUG 0 8 1984

RECEIVED

••	*****	**********	*****	• • • • • • • •	******
(for	official	use	only))

		- / -		
STATE OF OREGON CLAC	AUG 0 8 1984	25/RE	-12ca	
WATER WELL REPORT (as required by ORS 537.765) 0 4052 WAT	ER RESOURCES DEPT SALEM, OREGON	(for official		
(1) OWNER:	(10) LOCATION OF WELL by lega	l descript	ion:	
Name Fred and Ray Schoppert	County Clackamas NE 4 SW 44	_		
Address Route 1, Box 12	Township 2-South Range 2-	East	WM.	
City Linden, North Carolina State 28356	(Township is North or South)	(Range is East or V	West)	
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address) Rock	Creek &	S R 122m	
	MAILING ADDRESS OF WELL (or nearest address)	OLOGA G		
New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.	Drillers Well #19-84			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLET	ED WEL	L:	
Rotary Air Driven Domestic T Industrial Municipal D	Depth at which water was first found 151 ft.			
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level 61 ft. below	land surface. Da	ate 7-13-84	
Other: Other: Grounding Test	Artesian pressure — lbs. per	square inch. Da	ate	
(5) CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below ft. Depth of the De	v casing 6-ix f completed well		
Threaded ☐ Welded Z 6. Diam. from 116 ft. Gauge •250	Formation: Describe color, texture, grain size and structure and nature of each stratum and aquifer penetrated, with at formation. Report each change in position of Static Wat	least one entry fo	or each change of	
"Diam. from	water-bearing strata.		- •	
LINER INSTALLED: Steel	MATERIAL	From To	SWL	
4 Diam from 96 ft to 176 ft Gauge 188	Clay: brown	0	9	
	Cemented-gravel and boulders	9 3	il.	
(6) PERFORATIONS: Perforated? ✓ Yes □ No Size of perforations 1/8 in. by 7 in.	Clay: brown		6	
96 perforations from 136 ft. to 175 ft.	Clay: gray	76 10	71	
	Sand; grey, fine	104 10		
perforations from	Clay: grey	107 15		
	Sandstone; grey, brown	151 17	-	
(7) SCREENS: Well screen installed? Yes No	Clay: blue	173 17	76	
Manufacturer's Name				
Type			 	
Diam. Slot Size Set from ft. to ft. t				
Drawdown is amount water level is lowered	r -			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes No If yes, by whom?				
ld: gal./min. with ft. drawdown after hrs.				
, , , , , , , , , , , , , , , , , , ,	A			
Air test gal./min. with drill stem at ft. hrs.				
Bailer test 30 gal./min. with 104 ft. drawdown after 1 hrs.				
Artesian flow g.p.m.				
nperature of water 53° Depth artesian flow encountered	Date work started JULY 10. 1981 (complete	7 70.7 7	7 7 0%	
(9) CONSTRUCTION: Special standards: Yes No 🕱		d July 1	3, 1984	
Well seal—Material used Cament grout			19 84	
Well sealed from land surface to	(unbonded) Water Well Constructor Certifica			
Diameter of well bore to bottom of sealin.	This well was constructed under my direct sup information reported above are true to my best kno			
Diameter of well bore below seal		_		
Amount of sealing material sacks pounds	[Signed]	Date	, 19	
How was cement grout placed?Pumpad	(bonded) Water Well Constructor Certification	on:		
Canada Danas Tua	Bond 7560982 Issued by: Great A	merican	*****	
Sanetel Pumps, Inc.	l	ety Company Nan	•	
Was pump installed? NO Type Jat HP Depth ft.	Drilling Co. (type or print name of Wa	iter Well Construc	man Bros.	
Was a drive shoe used? Yes □ No Plugs Size: location	This well was drilled under my jurisdiction a	nd this renow	is true to the	
Type of Water? depth of strata	best of my knowledge and belief	Toport ours report	/	
Method of sealing strata off	(Signed) Vandel The for	-ell		
Was well gravel packed? Yes No Size of gravel:	Ronald F. McConnell (Water Well Construct	or)Ore. Ti	0.#1	
Gravel placed from	(Dated) August 6, 1981		- 1-r	
NOTICE TO WATER WELL CONSTRUCTOR	WATER RECOILERED TERAPTMENT		OD110555	