

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

RECEIVED

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

CLACKAMAS
4108

STATE OF OREGON
(Please type or print)
SALEM, OREGON

MAR 3 1975
State Well No. 2S/2E-14bb
State Permit No.

(1) OWNER:

Name Central Pre-Mix Concrete Co.
Address 16795 S. E. 130th, Clackamas, Or. 97015

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

6" Diam. from 0 ft. to 151 ft. Gage 0.250
5-9/16" Diam. from 150 ft. to 160 ft. Gage 10

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Table with columns: Size of perforations, in. by, in., ft. to, ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Johnson
Type Stainless Model No.
Diam. 6 Slot size 30 Set from 160 ft. to 170 ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Baller test 35 gal./min. with 120 ft. drawdown after 3 hrs.
Artesian flow g.p.m.
Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 3 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 7-75
NW 1/4 NW 1/4 Section 14 T. 2S R. 2E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 160 ft.
Static level 21 ft. below land surface. Date 2/12/75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing ---
Depth drilled 170 ft. Depth of completed well 170 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Cement, gravel and boulders, Clay, blue, Clay, grey, Sand, coarse, black.

Work started Jan. 16 1975 Completed Feb. 18 1975
Date well drilling machine moved off of well Feb. 19 1975

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Jack Durs Date Feb. 28, 1975
(Drilling Machine Operator)
Drilling Machine Operator's License No. 67

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Steinman Bros.
(Person, firm or corporation) (Type or print)
Address 14912 S.E. Kellogg Ave., Milwaukie, Or. 97222
[Signed] Robert E. McConnell
(Water Well Contractor)
Contractor's License No. I Date Feb. 28, 1975