WATER WELL REPORT STATE OF OREGON

CLA 04256

RECEIVED SEP 2 9 1982

State Well No.

25/2E-22

WATER RESOURCES DEPTState Permit No. SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name PHIL SETERA	County CLACKAMAS Driller's well	$\frac{1}{2}$	0
Address 14714 5 FORSYTHE RO.	4 4 Section 22 T. 2 S	R 2E	W.M.
City OREGON CITY State OREGON	Tax Lot # Lot. Blk	Subdivision	<u>1</u>
(2) TYPE OF WORK (check):	Address at well location:		
New Well ☑ Deepening □ Reconditioning □ Abandon □		11	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well. Denth at which water was first found 388 ft.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Departed many transfer of the second		
``	Static level 305 ft. below land surface. Date 8/28/82 Artesian pressure lbs. per square inch. Date		
Test Well Dug Irrigation Test Well Other			
Bored	(12) WELL LOG: Diameter of well below casing		
(5) CASING INSTALLED: Steel X Plastic _ □	Depth drilled 400 ft. Depth of completed well 400 ft. Formation: Describe color, texture, grain size and structure of materials; and show		
Threaded 🖂 Welded 🕱	thickness and nature of each stratum and aquifer pene	trated, with at leas	st one entry
Diant. Hom.	for each change of formation. Report each change in and indicate principal water-bearing strata.	osition of Static V	Water Level
4" Diam. from 3.75 ft. to 3.80 ft. Gauge Fix		T	
LINER INSTALLED:	MATERIAL	From To	SWL
"Diam from ft. to ft. Gauge	TOP SOIL	0 2	
(6) PERFORATIONS: Perforated? □ Yes No	BROWN CLAY	2 48	
Type of perforator used	CAY AND GRAVEL	48 130	
Size of perforations in. by in.	BUE CLAY	130 201	
perforations from	CEMENTED GRAVEL	201 311 311 323	
perforations from	DUE CUAY	<u> </u>	
perforations from	SANDY PLUE CLAY		
(7) SCREENS: Well screen installed? Yes 🗆 No	EAULAN BUILT (1AV	369 381 381 385	
Manufacturer's Name	LISON SOF BUIL	por 1900	
Type PLASTIC Model No.	SAWDSTONIE	385397	305
Diam. 4 Slot Size 10 Set from 380 ft. to 400 ft.	BLUE CLAY	397 400	
Diam. Slot Size Set from ft. to ft. to ft.	JELL CS.		
Drawdown is amount water level is lowered			
(8) WELL TESTS: below static level			
a pump test made? Yes No If yes, by whom?			
gal/min. with ft. drawdown after hrs.			
Air test gal/min, with drill stem at ft. hrs.		 	
Bailer test /6 gal./min. with 25 ft. drawdown after / hrs.		ļ	
tesian flow g.p.m.	7/2	100	
reinperature of water Depth artesian flow encountered ft.	Work started 7/6 19 82 Complet	$\frac{1}{2} \frac{7}{2} \frac{28}{2}$	
(9) CONSTRUCTION: Special standards: Yes \(\text{No.} \)	Date well drilling machine moved off of well	<u>1128 </u>	1982
Well seal—Material used CEMENT / 3 / BENTONITE	Drilling Machine Operator's Certification:	•	
Well sealed from land surface toft. Dismeter of well hore to bottom of sealin.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.		
Billineter of weil bote to bottom of both	[Signed] Date 8/7, 19.82		
Diameter of well bore below sealin.	(Drilling Machine Operator)		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No	<u> </u>	*******
How was cement grout placed?	Water Well Contractor's Certification:		
The state of the s	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was pump installed? YES Type SUB HP 1/2 Depth 357 ft.			
Was a drive shoe used? Yes □ No Plugs Size: location ft.			
Did any strata contain unusable water? Yes No	Address 6350 SE BROWNLEE MILW AUKIE		
Type of Water? depth of strata	I resimual Dekoon		
Method of sealing strata off	[Signed] (Water Well Contract	tor) e) /	₩
Was well gravel packed? X Yes \(\text{No} \) Size of gravel: \(1.4	Contractor's License No. 442. 4. Date	O/l	,19.02
Gravel placed from 3/5 ft. to 400 ft.			