

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON
(Please type or print)

(Do not write above this line)

JUN 26 1974

State Well No.

25/2E -22 dd

CLAC
04276

STATE ENGINEER
SALEM, OREGON

State Permit No.

(1) OWNER:

Name JACK SIRI
Address 15583 S FORSYTHE RD
OREGON CITY, OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

8" Diam. from 0 ft. to 161 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Type of perforator used MILLS KNIFE
Size of perforations 2 in. by 1/4 in.
300 perforations from 118 ft. to 160 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? SIRI
Yield: 100 gal./min. with 50 ft. drawdown after 11 hrs.
" " " " " " " "
" " " " " " " "
Baller test 75 gal./min. with 15 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 10 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County CLACKAMAS Driller's well number 300
SE 1/4 SE 1/4 Section 22 T. 25 R. 2E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 121 ft.
Static level 84 ft. below land surface. Date 6/17/74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 165 ft. Depth of completed well 165 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	1	
RED CLAY	1	16	
BROWN CLAY	16	47	
GRAY BASALT	47	110	
BROWN CLAY	110	118	
LOOSE GRAVEL	118	157	84
BLUE CLAY	157	165	

Work started 8/10 19 73 Completed 6/17 19 74
Date well drilling machine moved off of well 6/17 19 74

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Ockell Date 6/24, 19 74
(Drilling Machine Operator)
Drilling Machine Operator's License No. 329

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name KAUFER WELL DRILLING CO.
(Person, firm or corporation) (Type or print)
Address 5365 S.E. Hillwood MILWAUKIE
[Signed] Ockell
(Water Well Contractor)
Contractor's License No. 462 Date 6/24, 19 74