OCT 11 1978 State Well No. 25/2E-236c STATE OF OREGON WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 (Please type or print) 04285 (Do not write above this line R RESOURCES DEFINITION. within 30 days from the date of well completion. SALEM. OREGON (10) LOCATION OF WELL: (1) OWNER: CountyClackamas Driller's well number D-150-78 Name David E. Fletcher SW 14 NW 14 Section 23 T. 2S R. Address 16453 S. Forsythe Rd. 2E Oregon City, Oregon 97045 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Taxlot 00100 Deepening [Reconditioning [Abandon | New Well 😾 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): 97 (3) TYPE OF WELL: Depth at which water was first found ft. below land surface. Date 9-22 276 Rotary Driven | Static level Domestic 🎩 Industrial 🗌 Municipal 🗍 Jetted 🔲 Cable Irrigation | Test Well | Other lbs, per square inch. Date Bored [Artesian pressure Dug CASING INSTALLED: (12) WELL LOG: Threaded □ Welded □ X Diameter of well below casing 6 " Diam, from 02 ft. to 52 ft. Gage ... 250 ft. Depth of completed well Depth drilled 5 " Diam. from 55 ft. to 355 ft. Gage 188 Formation: Describe color, texture, grain size and structure of materials; "Diam. from _____ft. to _____ft. Gage ____ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? M Yes | No. MATERIAL Type of perforator used torch 2 in. by 1/8 Topsoil Size of perforations 10 17 32 perforations from 355 ft. to 335 clay brown 21 Basalt Gray perforations from _____ ft. to ____ 21 49 Clay Brown perforations from _____ ft. to ____ 49 63 Basalt Brown (7) SCREENS: 97 Well screen installed? | Yes | No 63 Cindres Red Manufacturer's Name 97 116 Basalt Gray trace/water 116 cinders Red 134 Diam. _____ Slot size _____ Set from ____ ft. to _____ ft. basalt Gray Rock Red Fractured 177 209 Diam. Slot size Set from ft. to ft. 328 209 Basalt Gray hard Drawdown is amount water level is lowered below static level (8) WELL TESTS: 328 334 Sandstone & Chay Brown Gravel&Sand Waterbearing 334 355 Was a pump test made? X Yes \(\subseteq \text{No If yes, by whom?} \) AquaPump gal./min. with 41 ft. drawdown after 2½ gal./min. with ft. drawdown after Bailer test g.p.m. Artesian flow 9/21 19 78 9/159 78 Completed perature of water Depth artesian flow encountered ft. Work started Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Cement This well was constructed under my direct supervision. Materials used and information reported above are true to my and belief.

Stock Date // 10/78

(Drilling Machine Operator) Diameter of well bore to bottom of seal _____in. best knowledge and belief. Diameter of well bore below seal6 Number of sacks of cement used in well seal _______5___sacks Drilling Machine Operator's License No.1169...... How was cement grout placed? poured Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name S&M Drilling & Supply Inc.

(Type or print) Was a drive shoe used? XYes \(\subseteq \text{No Plugs} \text{Size: location ft. Did any strata contain unusable water?

Yes 💆 No Address 399SE Walnut St. Canby, Oregon 97013 depth of strata Type of water? Method of sealing strata off Was well gravel packed? Yes No Size of gravel: Contractor's License No. 497 Date 10/10, 19.78 Gravel placed from ft. to ft.

LAC WATER WELL REPERECEIVED

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the