04414

30B

State Well No.

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

ST. TE E 'GINEER

STATE OF OREGON G 2024

State Permit No. .

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name CHARLES F. THOMAS	Was a pump test made?  Yes No If yes, by whom?
Address RIVER ROAD, GLADSTONE, OREGON	Yield: gal./min. with ft. drawdown after hrs.
	27 25 27 21
(2) LOCATION OF WELL:	Bailer test 60 gal./min. with 1 ft. drawdown after 3 hrs.
County Clackamas Owner's number, if any G-2024	Artesian flow g.p.m. Date
1/4 1/4 Section 19 T. 2 S. R. 2 E. W.M.	Temperature of water Was a chemical analysis made? ☐ Yes ☐ No
Bearing and distance from section or subdivision corner	3.0
	(12) WELL LOG: Diameter of well 10 inches.
, , , , , , , , , , , , , , , , , , , ,	Depth drilled 64 ft. Depth of completed well 56 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Top soil 0 2
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 11.	med. gravel, coarse sand clay bind 26 40
	free gravel and sand 40 61
PROPOSED USE (check): (5) TYPE OF WELL:	Red clay 61 64
Domestic	
Irrigation Test Well   Other   Dug   Bored	
(6) CASING INSTALLED: Threaded □ Welded ■	
(6) CASING INSTALLED: Threaded   Welded   10, Diam. from   0   ft. to   56   ft. Gage   2	
"Diam from ft. to ft. Gage	
"Diam. fromft. toft. Gage	
(7) PERFORATIONS: Perforated? 至 Yes 口 No Type of perforator used 光光光光 To <sup>rch</sup>	
Type of perfect about 1122	
SIZE of perforations 8"X8" in. by in.  120 perforations from 36/3 ft. to 56/2 ft.	
perforations fromft. toft.	
(8) SCREENS: Well screen installed ☐ Yes 🖹 No	
Manufacturer's Name	
Type Model No ft. to ft.	
Slot size Set from ft. to ft.	Work started April 14 19 61 Completed Apr. 27/1961
(a) CONSTITUTION.	(13) PUMP:
(9) CONSTRUCTION: Was well gravel packed?  Yes  No Size of gravel:	Manufacturer's Name Fairbanks-Morse
Gravel placed from 56 ft. to 64 ft.	Type: Submersible Turbine H.P. 15
s a surface seal provided? Yes No To what depth? 20 ft.	and the second s
Material used in seal— CLEY	Well Driller's Statement:
Did any strata contain unusable water? □ Yes 祝 No	This well was drilled under my jurisdiction and this report is
Type of water? Depth of strata	true to the best of my knowledge and belief.
Method of sealing strata off	NAME Skyles Drilling & Supply  (Person, firm, or corporation) (Type or print)
(10) WATER LEVELS: 1961 Static level 34 ft. below land surface Date April 27	Address 19215 S. E. McLoughlin Blvd.
Static level 54 ft. below land surface Date APFLI 27  Artesian pressure lbs. per square inch Date	Gladstone, Oregon Driller's well number
Log Accepted by:	Harrie III Stanley
Isia Thas that Thomas June 7 1961	[Signed] (Well Driller)
(Owner)	License No. 58 Date April 27, 1961