

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

CLAC

WATER WELL REPORT

STATE OF OREGON

RECEIVED
JUN 26 1974

State Well No. 25/3E-6 bb

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

04605

(Please type or print)

(Do not write above this line) STATE ENGINEER SALEM, OREGON State Permit No.

(1) OWNER:

Name JOHN BROCKAMP
Address 12596 S.E. 162
CLACKAMAS OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

6" Diam. from +1 ft. to 89 ft. Threaded Welded
Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Bailer test 22 gal./min. with 2 ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 7 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County CLACKAMAS Driller's well number 299
NW 1/4 NW 1/4 Section 6 T. 25 R. 3E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 93 ft.
Static level 86 ft. below land surface. Date 5/17/74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 222 ft. Depth of completed well 222 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	2	
BROWN CLAY	3	18	
CLAY AND BOULDERS	18	55	
LOOSE GRAVEL	55	77	
GRAY BASALT	77	92	
BROKEN BLACK BASALT	92	97	86
GRAY BASALT	97	222	86

Work started 5/15 19 74 Completed 5/17 19 74
Date well drilling machine moved off of well 5/17 19 74

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Edward Schmitt Date June 7, 1974
(Drilling Machine Operator)
Drilling Machine Operator's License No. 564

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name KELLER WAL DRILLING CO. (Type or print)
Address 5365 S.E. HILWOOD MILWAUKIE
[Signed] CE Kell (Water Well Contractor)
Contractor's License No. 462 Date 6/6, 1974

(USE ADDITIONAL SHEETS IF NECESSARY)