WATER WELL REPORT CEIVED NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF OREGON NOV 2 1 1979 State Well No. 3 WATER RESOURCES DEPARTMENT, (Do not write above this line) RESOURCES SHEPTermit No. SALEM, OREGON 97310 within 30 days from the date of well completion. SALEM, OREGON (10) LOCATION OF WELL: (1) OWNER: Driller's well number 52-79 County Clackamas Name Roger R. Robbins т 2-8 в. 3-1 Address Route 1, Box 286-1, Beavercreek, Oregon 14 NW 14 Section 7 W.M. 97001 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Reconditioning [ Abandon 🗀 Deepening [ New Well IX If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): Depth at which water was first found (3) TYPE OF WELL: ft. below land surface. Datel 0-18-79 Static level 377 106 Driven 🛚 Rotary Domestic | Industrial | Municipal | Jetted Irrigation 🛛 Test Well 🗌 Other lbs. per square inch. Date Artesian pressure Bored 🔲 (5) CASING INSTALLED: (12) WELL LOG: Threaded | Welded | Diameter of well below casing ..... 8 "Diam. from +1 ft. to 332 ft. Gage •250 ft. Depth of completed well 357 Depth drilled " Diam. from ...... ft. to ..... ft. Gage ... Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? Tyes No. From MATERIAL Type of perforator used 2 in. by Top soil Size of perforations 2 13 Clav: tan perforations from ...... ft. to ..... ft, 19 13 perforations from \_\_\_\_\_\_ft. to \_\_\_\_\_ft. Clay: brown, sticky 26 19 Clay: tan, granular perforations from ...... ft. to ...... ft, 26 160 Conglomorate (7) SCREENS: 160 173 Well screen installed? X Yes No Clav: brown Manufacturer's Name Johnson 173 192 Clay: green, sandy Type Stainless Steel - 30LSS Model No. 192 226 Clay: grey, sandy Diam. 8 Slot size • 0010 Set from 333 ft. to 3111 226 275 Clay: grey Diam. ..... Slot size ..... Set from ..... ft. to ..... ft, to 1.0/ 5/75 253 Sand and gravel, dirty 253 309 Clav: grey, sticky Drawdown is amount water level is lowered below static level Steinman (8) WELL TESTS: 331 309 Clay: green, sticky 334 331 s a pump test made? 🛛 Yes 🗌 No If yes, by whom? Bros. Sandstone: dark grev 106 334 345 Sand: loose, fine gal./min. with 206 ft. drawdown after 8 hrs. Clay: green gal./min. with ft. drawdown after Bailer test g.p.m. Work started Sept. 27, 1979 Completed Oct. 26, Temperature of water 5110Depth artesian flow encountered ...... ft. 19 79 Date well drilling machine moved off of well October 26, (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Coment This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to 22 Diameter of well bore to bottom of seal 12 in. best knowledge and belief.

[Signed] Land Machine Operatory

Glenn D. Rydmen Machine Operatory

Drilling Machine Operator's License No. 54 Diameter of well bore below seal 8 in. How was cement grout placed? Pumped through a one inch plastic pipe between the twelve inch hole and Water Well Contractor's Certification: the eight inch casing. This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Steinman Bros. Drilling Co.
(Type or print) Was a drive shoe used? M Yes [] No Plugs ...... Size: location ...... ft. Did any strata contain unusable water? Tyes I No Address 3023 S. E. Holly Avenue, Milwaukie, Oregon Type of water? Method of sealing strata off Ronald F. McConnell (Water Well Contractor) [Signed] . Was well gravel packed? [] Yes X No Size of gravel: ...... Contractor's License No. 1 Date Nov. 19. , 19.79