NOTICE TO WATER WELL CONTRACTOR The original and first copy of the perfect to th	II PEDADA /	E 1		
WATER RESOURCES DEPARTMENT APR 6 1979 STATE OF SALEM, OREGON 97310 APR 6 1979 (Please type within 30 days from the date	OREGON CLASS State Well No.	0	E-9 .849	9C
of well completionWATER RESOURCESDEPWrite a	hove this line) 04682 State Permit 1	NO\		
SALEM, OREGON	T /			
(1) OWNER:	(10) LOCATION OF WELL:			
Name DAMASCUS WATER DISTRICT	County Clackamas Driller's well n	umber D	-200-	- 79
Address 19750 SE Damascus Lane Boring, Oregon 97009	SW/ 1/4 NE 1/4 Section 9 T. 2S	R. 3E		W.M
	Bearing and distance from section or subdivis	ion corne	r	-
(2) TYPE OF WORK (check):	well #6-A			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				• •
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	vell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Denth at which water was first forms 50			
Rotary Driven Domestic Industrial Municipal	66		- 4-	-3 - 7
Cable				
	Artesian pressure lbs. per squa	re inch.	Date	
CASING INSTALLED: Output Threaded Welded 322 ft. to 162 ft. Gage 322	(12) WELL LOG: Diameter of well 212	below cas	ing 212	8
"Diam. from 160 ft. to 210 ft. Gage .188	20pm drifted 1t. Depth of comp	teted well		11
ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	ım and a	guifer n	enetrated
PERFORATIONS: Perforated? Yes XX0.	with at least one entry for each change of forms position of Static Water Level and indicate prin	tion, Rend	ort each	change in
Type of perforator used	MATERIAL	From	То	swl
Size of perforations in. by in.	top soil	0	2	
perforations from ft. to ft.	clay gravel lg. cobbles	2	50	
perforations from ft. to ft.	gravel water	50	86	
perforations from ft. to ft.	clay brown	86	97	
(7) SCREENS: Well screen installed? XVer D No.	claystone water	97	106	
Tell serven instance — Tes () 140	sandstone basalt decompos	ed		
SCI EEN 304 -1-1	w/water	106	122	
Type 8" tele 100 1765el No. 30478tain-		122	135	
Diam. So solve 100 Set from 191 ft. to 193 ft. Diam. Slot size 80 Set from 193 ft. to 195 ft.	sand course multicolor			
	gravel sand water	135	156	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	sandstone brown water	156	165	
Was a pump test made? Yes No If yes, by whom? Aqua Pump	sandstone brown fractured			
Viold: 500 24	gravel large sand brown	165	170	
arawaswa anga ms.	fine water	170	100	
" " "	gravel lg, sand brown med.		180	
n n n	W/ Water	180	192	
Bailer test gal./min. with ft. drawdown after hrs.	gravel lg. little sand			
Artesian flow g.p.m.		192	196	
perature of water Depth artesian flow encounteredft.	Work started 3-/3 1979 Complete			1979
(0) CONSUDICATION	Date well drilling machine moved off of well	<u> </u>	<u>-</u> /	1979
(9) CONSTRUCTION:		7-	7	19/7
well seal—Material used	Drilling Machine Operator's Certification:			
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	This well was constructed under my Materials used and information reported best knowlydge and belief	direct above a	super re true	vision. to my
Diameter of well bore below seal in.	[Signed] And Sonnelly	Date		. 19
Number of sacks of cement used in well seal	(Drilling Machine Operator			-
How was cement grout placed? Pumped by pressure	Drilling Machine Operator's License No			
T. T	Water Well Contractor's Certification:			
Was a drive shoe used? Yes ☐ No Plugs Size: location ft.	This well was drilled under my jurisditrue to the best of my knowledge and beling & State of Manager 1997 and 1997 and 1997 and 1997 are the state of the state o	ction and	l this re	eport is
Did any strata contain unusable water? Yes \ No	14011C			
	Address 399 SE Walnut Canby	, Ore	e or prin	t)
	Address			
Method of sealing strata off	[Signed] Walter More			
Was well gravel packed? [] Yes 🖔 No Size of gravel:	(Water Well Confr	-		
Gravel placed fromft. to ft.	Contractor's License No497 Date	1-470		, 19

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State_Well	No
State Perm	nit No

	•			
(1) OWNER:	(10) LOCATION OF WELL:			
Name DAMASCUS WATER DISTRICT	County Driller's well nu	ımber		
Address 19750 SE Damascus Lane Boring, Oregon 97009	34 34 Section T.	R. W.M.		
	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.		
Rotary Driven Domestic Industrial Municipal	Static level ft. below land s			
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	pelow casing		
	Depth drilled ft. Depth of completed well ft.			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials:			
PERFORATIONS: Perforated? Yes No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used	MATERIAL	From To SWL		
Size of perforations in. by in.	clay grey	196 206		
perforations from ft. to ft.	sand black water	206 208		
perforations from ft. to ft.	clay blue	208 210		
perforations from ft. to ft.				
(7) SCREENS: Well screen installed? \(\sigma\) Ves \(\sigma\) No				
Manufacturer's Name				
Type Model No.				
Diam Slot size Set from ft. to ft.				
Diam, Slot size Set from ft. to ft.	DECEIVED			
(8) WELL TESTS: Drawdown is amount water level is	KEULIVLU			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	APR 61979			
Was a pump test made? Yes No If yes, by whom?		от		
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES CH			
" " "	SALEM. OREGUN			
, n n n				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started 3-13- 1979 Complete	d 4-4- 19 79		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-4 19 79		
Well seal—Material used	Drilling Machine Operator's Certification:			
Well sealed from land surface to ft.	This well was constructed under my	direct supervision.		
Diameter of well bore to bottom of seal in.	Materials used and information reported best knowledge and belief.	above are true to my		
Diameter of well bore below seal in.	Land V / a like	Date 4-4- 19.79		
Number of sacks of cement used_in well seal sacks	(Drilling Machine Operator)			
How was cement grout placed?	Drilling Machine Operator's License No			
	Water Well Contractor's Certification:			
Was a drive shoe used? □ Ves □ No Diver	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	Name S & M DRILLING & SUPPLY, INC.			
	(Person, firm or corporation) (Type or print) 399 S.E. Walnut St. Canby, Or.			
	Address			
Method of sealing strata off	- [Signed] Malle Miles			
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No Date	44 , 1979		