RECEIVED

STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

CLAC 50474

APR 29 1996

Instructions for completing this report are on the last page of MATER RESOURCES DEPT. OREGON
(9) LOCATION OF WELL by legal description: SALEM (1) OWNER: Well Number County Clackamas Latitude_ Longitude Name A. McGill & Sons N or S Range 1W E or W. WM. Township Address 31223 S.Meridian Rd 1/4 NE 1/4 NW State OR Zip 97032 Section City Hubbard Subdivision Tax Lot Lot Block (2) TYPE OF WORK X New Well Deepening Alteration (repair/recondition) Abandonment Street Address of Well (or nearest address) 31223 S. Meridian Rd. (3) DRILL METHOD: Hubbard, OR (10) STATIC WATER LEVEL: Rotary Mud X Cable Auger Rotary Air Date 4/12/96 57 ft. below land surface. Other (4) PROPOSED USE: Artesian pressure lb. per square inch. (11) WATER BEARING ZONES: Community Industrial x Irrigation Domestic Other Livestock Thermal Injection Depth at which water was first found 31' (5) BORE HOLE CONSTRUCTION: Special Construction approval Yes No Depth of Completed Well 160 ft. SWL Estimated Flow Rate From Explosives used Yes XX No Type Amount 31' 38! 10 ggm 8' HOLE SEAL 105' 57' To Sacks or pounds 129' Diameter From Material From 400 qpm 20" 80 Bentonite Ω 50 chips 50 80 25 sacks cement 16" 201 80 (12) WELL LOG: $\square D$ \Box B $\mathbf{Z}^{\mathbf{C}}$ \Box E How was seal placed: Method A Ground Elevation . K Other OAR 690-210-340 То **SWL** From Material Material Backfill placed from ____ ft. to Clay brown 0 Size of gravel Gravel placed from 7 17 (6) CASING/LINER: Clay grey Clay brown, gravel 17 21 Welded Plastic Threaded Diameter From To Gauge Steel Clay sandy brown 21 31 105 : 375 $\Box \mathbf{x}$ +2' 16" Casing:_ 81 Sand/silt brown 31 38 П 38 55 Clay sandy grey 55 60 Clay grey, gravel Clay grey 60 62 Liner: Clay sandy grey 62 67 Sand black & gravel 67 70 Final location of shoe(s) 105' Gravel, clay grey 70 75 (7) PERFORATIONS/SCREENS: 75 81 Clay brown Perforations Method Clay grey, gravel 81 89 Material Stainless ★ Screens Type Tele/pipe 89 93 Slot Clay grey, sand Casing Liner To Number Diameter From size Clay grey, gravel 93 105 10" 105 pipe +2 57' 105 129 Sand black, gravel 115 10" 105 065 p.s. 129 147 Clay grey 10" 115 129 p.s. 152 Clay grey with sand layers 147 10" 129 160 pipe Clay sticky grey 152 201 160 | Bottom plate Completed (8) WELL TESTS: Minimum testing time is 1 hour Date started 2/23/96 (unbonded) Water Well Constructor Certification: Flowing I certify that the work I performed on the construction, alteration, or abandonment Pump Bailer ☐ Air Artesian of this well is in compliance with Oregon water supply well construction standards. Drill stem at Time Materials used and information reported above are true to the best of my knowledge Yield gal/min Drawdown 1 hr. and belief. 52' 400 WWC Number _ Temperature of water 54 Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work Yes By whom Was a water analysis done? performed on this well during the construction dates reported above. All work Did any strata contain water not suitable for intended use? Too little performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief. Salty Muddy Odor Colored Other 783 WWC Number Depth of strata: Date 4/23/96 Signed