RECEIVED

	TAG # L	07078
STATE OF OREGON CLAC JAN		
WATER SUPPLY WELL REPORT 5/28	(START CARD)#	62424
(as required by ORS 537.765) Instructions for completing this report are on the last page of this Vortice RE SALE	SOURCES DEPT.	
Instructions for completing this report are on the last page of this service SALE	M OREGON (5) LOCATION OF WELL by legal descrip	tion:
1) OWNER:	County CLACKAMAS Latitude	
Name Neuschwander's Nursery	Township 45 N or S Range 19	E or W. WM.
Address 6097 S. Whiskey Hill Rd State Or Zip 97032	Section 32 Se 1/4	Nw 1/4
City Number u	Tax Lot 900 Lot Block	Subdivision
(2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonment Abandonment 20435 S. Noedy, Rd		
A SPATA MERCHADA		
Rotary Air Rotary Mud X Cable Auger	(10) STATIC WATER LEVEL:	D
Other	47 ft. below land surface.	Date <u>Sep 10, 19</u> 96
(4) PROPOSED USE:	Artesian pressure lb. per square	inch. Date
Domestic Community Industrial Irrigation	(11) WATER BEARING ZONES:	
Thermal Injection Livestock Other	Depth at which water was first found40	
(5) BORE HOLE CONSTRUCTION:	Depin at which water was instituted	
Special Construction approval Yes No Depth of Completed Well 140 ft.	From To	Estimated Flow Rate SWL
Explosives used Yes No Type Amount SEAL	40 140	47
Diameter From To Material From To Sacks or pounds 12 1 50 Bentonite 1 50 35 sacks		
8 50 140		
	(12) WELL LOG:	
How was seal placed: Method A B C D E	Ground Elevation	
Other Granular Bentonite method	Material	From To SWL
Backfill placed from ft. to ft. Material	Soi 1	1 3
Gravel placed from 60 ft. to 120 ft. Size of gravel nea	Clay, Brown	3 38
(6) CASING/LINER:	Cemented gravel, brown	38 54
Diameter From 10 Gauge Steel Fluste	Clay, grey	54 58
Casing: 0 140 .25 k	Clay, grey, sandy	58 60
	Sand, black, fine	60 69
	Sand and gravel, black	69 71
Liner:	Cemented gravel, sand	71 74
	Sand & gravel	74 95 95 98
Final location of shoe(s) 140	Clay, blue	95 98 98 101
(7) PERFORATIONS/SCREENStive Down	clay, grey, silty	101 108
Perforations Method	Silt, dark grey Clay w/black coarse sand	108 116
Storeens Type Material Tele/plpe	Clay, grey w/some cemented gr	
Slot From To size Number Diameter size Casing Liner	Clay, blue	136 140
76 117 1.100 000	0.4, (= = =	
	Note: 6 inch gravel feed eac	h side of
	8 inch well	
	August 8, 1996 Comp	Dec 10, 1996
(8) WELL TESTS: Minimum testing time is 1 hour	Date started	leteu
Flowing	(unbonded) Water Well Constructor Certificat	ion:
Pump Bailer Air Artesian	I certify that the work I performed on the cons of this well is in compliance with Oregon water s	
Yield gal/min Drawdown Drill stem at Time	Materials used and information reported above at	re true to the best of my knowledge
1 d bn	and belief. WWC Number	
220 105 4 11	Signed	Date
(bonded) Water Well Constructor Certification:		
Temperature of water 53 Deput Alteration or abandonment work		
was a water analysis doller. The little performed on this well during the construction dates reported above. The well performed on this well during the construction dates reported above.		
Did any strata contain water not suitable for intended use? Too little performed during this time is in compliance with Oregon water supply well performed during this time is in compliance with Oregon water supply well construction standards. This report is any to the best of my knowledge and belief.		

THIRD COPY-CUSTOMER

Salty Muddy Odor Colored Other

Depth of strata: