WATER WELL REPORT CT 20 19

2/3#- 28M2

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion. OCT

State Well No. State Permit No.

OZ WOJZ COZNOJENOJI,			****************	***************************************
(1) OWNER:		(11) WELL TESTS: Drawdown is amount	water leve	el is
Name Logan Egg Farm		lowered below static level Was a pump test made? ▼ Yes □ No If yes, by whom? driller		
Address Rt. 5 Box 518		Yield: 400 gal./min. with 90 ft. drawdow		/3 hrs.
Oregon City, Oregon		<u>" 90 " 90 "</u>	1	/3
	?	" " " " "		"
(2) LOCATION OF WELL:		Bailer test 50 gal./min. wit8_10 ft. drawdov	vn after	7 / A hrs
County Clack anns Driller's well number		Artesian flow g.p.m. Date	111 (11,001	3/4
¼ ¼ Section 28 T. 2	S R. 3 N W.M.	Temperature of water Was a chemical analysis r	made2 🗖	Ves X No
Bearing and distance from section or subdivision	corner	The a chemical analysis i	naue:	165 23 110
	·	(12) WELL LOG: Diameter of well below c	asing	***************************************
		Depth drilled 227 ft. Depth of completed w	rell 15	O ft.
		Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	il and stri the mater hange of	icture, and ial in each formation.
	4 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	- MATERIAL -	FROM	то
(3) TYPE OF WORK (check):		Sandy clay soil	_	3
New Well Deepening Reconditioning Abandon		decomposed sand	3	27
pandonment, describe material and procedure		rocky clay	27	75
		part cement gravel & water	75	80
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	rocky clay	80	112
Domestic 🗌 Industrial 🔀 Municipal 🔲	Rotary Driven Cable Jetted	water-bearing sandstone	112	127
Irrigation ☐ Test Well ☐ Other ☐	Cable	sandstone nonwaterbearing	127	
		grey silty clay	-	145
	ded 🗌 Welded 🍒	grey brown clay	145	159
0ft. to7		cemented gravel	159	167
8) ft. Gage	brown sandy clay	167	173
	ft. Gage	comparted amount	173	201
(E) DEDEOD AMEONG		cemented gravel	201_	227
	rated? 🗌 Yes 🔼 No	7	-	
Type of perforator used torch		Loss of static head was note	1	1
Size of perforations 1/8 in. by 12		last day of drilling, backfi	lling	\$
900 perforations from 71		did not stop am loss of hea	d so	
60 perforations from131		- Well was filled to 150.	l	
perforations from				
perforations from	• • • •			
perforations from	ft. to ft.			
(8) SCREENS: Well screen instal	lled 🗌 Yes 🗶 No			
Manufacturer's Name				
Model				
11 Slot size Set from		Work started Q/A/CA 10 Completed 2 Completed 2		10
Diam. Slot size Set from ft. to ft.		Work started 9/4/64 19 . Completed 10/8/64 19		
		Date well drilling machine moved off of well 10/	8/64	19
(9) CONSTRUCTION:	· · · · · · · · · · · · · · · · · · ·	(13) PUMP:		
Well seal—Material used in seal Bentonite and clay		Manufacturer's Name		
Depth of seal		Туре: Н.Р.		
Diameter of well bore to bottom of sealin.				
Were any loose strata cemented off? [Yes 4 No Depth		Water Well Contractor's Certification:		
Was a drive shoe used? ☐ Yes X No		This well was drilled under my jurisdiction a	and this	report is
Was well gravel packed? Yes No Size of	gravel:	true to the best of my knowledge and belief.		-1
Gravel placed from ft. to		MANUE GROBER Zont & Conc		
Did any strata contain unusable water? 1 Yes		NAME George Zent & Sons (Person, firm or corporation) (T	ype or prin	
Type of water? Depth of stra	,	Address 4305 N E 44 th St. Vanco		
		VIII DU VALLE	W.A. Z.T.	:
Method of sealing strata off		Drilling Machine operator's License No. 205		••••••
(10) WATER LEVELS:	: . : :: :: ::	fillett & Ben		-
Static level 42 ft. below land sur	rface Date 9/9/64	[Signed] (Water Well Contractor)	/	<u></u>
Artesian pressure lbs. per square		Contractor's License No. 228 Date 10/	14/	Co Fel