WATER WELL REPORT AC STATE OF OREGON 05619

RECEIVED #4

State Well No. 25/4E-8bc

OCT 25 1983	State Permit No.	
LEASE TYPE OF PRINTING INK	Succe Crimo 4 to	

SALEN, Q	REGON			
(1) OWNER:	(10) LOCATION OF WELL:			
Name Iseli Nursery	County CLACKAMAS Driller's well	number		
Address 15 Q 41 S.E. TICKLE Creek	BSW4NW 4 Section 8 TAS	R. 4/	E	W.M.
City Borine State ORC	Tex Lot # Lot Blk	Su	bdivision	
	Address at well location:			
(2) TYPE OF WORK (check):				
New Well	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 230			ft.
	Static level 155 ft. below land surface. Date 8/8/83 Artesian pressure lbs. per square inch. Date			
Rotary Air Driven Domestic Industrial Municipal Industry Mud Dug Inrigation Test Well Other Industrial Reinjection Industrial Industrial Reinjection Industrial	Artesian pressure lbs. po (12) WELL LOG: Diameter of well below			-
	Depth drilled 353 ft. Depth of			37 ft.
(5) CASING INSTALLED: Steel 1 Plastic Threaded Welded 1 Welded 1 Welded 1 Threaded T	Formation: Describe color, texture, grain size and str thickness and nature of each stratum and aquifer pene for each change of formation. Report each change in	ucture of a	naterials th at leas	; and show t one entry
"Diam from	and indicate principal water-bearing strata.	T	1	
LINER INSTALLED:	MATERIAL	From	To	SWL
8."Diam. from Z90ft. to 337ft. Gauge 160. PSI. PVC	SOIL BROWN	0	7_	
(6) PERFORATIONS: Perforated?	CLAY BROWN	2	18	
Type of perforator used ROTARY STAR AND SAW	CEMENTED GRAVEL	18	150	
Size of perforations INV H in to 5 X / B in.	CLAY BROWN	150	120	
1300 perforations from 24.8. ft. to .292. ft.	CLAY BROWN W/ SOME FINE GRAVEL	150	205	
1.20 perforations from .7.90 ft. to .335 ft.		158	205	
perforations from ft. to ft,	SAUD COURSE W/SOME	205	758	155
(7) SCREENS: Well screen installed? Yes to No		AUS	230	105
Manufacturer's Name	CEMENTED GRAVEL W	258	Z92	155
TypeModel No.	SAUDSTONE BROWN HARD		299	
Diam. Slot Size Set from ft. to ft. to ft.	GRAVEL AND SAND		338	122
Diam. Slot Size	SAND FINE BROWN & GRAY		353	-/
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? □ Yes □ No If yes, by whom?	and the second s			
ld: gal./min. with ft. drawdown after hrs.	· ;			
, N				
Air test 300+ gal./min. with drill stem at 300 ft. hrs.	•			
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
mperature of water Depth artesian flow encountered ft.	Work started 7/20 19 83 Complete	ed 8	18	<u> 1983</u>
(9) CONSTRUCTION: Special standards: Yes 🗆 No 🔼	Date well drilling machine moved off of well	පී/	18_	<u> 1983</u>
Well seal—Material used CEMENT	(unbonded) Water Well Constructor Certif	ication	if appli	icable):
Well sealed from land surface to	This well was constructed under my direct	supervisi	on. Mate	rials used
Diameter of well bore to bottom of seal .1.5in.	and information reported above are true to my		$\sim L_{-}$	· (75°)
Diameter of well bore below seal 10	[Signed] (Mules)	Date	ندر <u>د</u>	19.83
Number of sacks of cement used in well seal	Bonded Water Well Constructor Certificat	ion:		
How was cement grout placed?	Bond 25466 Issued by: SA	FÇO)	
The second secon	(number) Su This well was drilled under my jurisdictio	rety Compan	•	ia tura ta
Ted - Cub-40 - 001	the best of my knowledge and belief.	i and th	re rehou∩	is title to
Was pump installed? Ted TypeSub. HP 40. Depth 301 ft.	Name 7ed Pull 17777 (vel		Illing
Was a drive shoe used? Tes \(\subseteq \text{No} \) Plugs Size: location ft. Did any strata contain unusable water? \(\subseteq \text{Yes} \) Yes	Address 4845 W. Powe	11 6		or print)
The second secon	8 1 2176	17/1		27.18.46.7.9.J.
Type of Water? depth of strata Method of sealing strata off	[Signed] Worm Wall County	~UC	m	<u>/</u>
Was well gravel packed? Yes Size of gravel: Size of gravel:	Water Well Constru Date		ノク	10 6 3
Gravel placed from	Date	7		, 100
The state of the s				