WATER WELL REPORT also Wall \$5 G 11241 MAR 28 1968 L File Original and First Copy with the STATE ENGINEER, SALEM, OREGON State Permit No. .. C 5 629 (11) WELL TESTS: Drawdown is amount water level is lowered below static level Bottner

Was a pump test made? D Yes No If yes, by whom? Drilling CO. (1) OWNER: Name Mr. Verner W. & Germaine Iseli Address 1610 N.E. 64th. Yield: 150 gal./min. with 0 ft. drawdown after hrs. Portland 13 Oregon 300 (2) LOCATION OF WELL: Epperson Rd. County (Vackames bowner's number, Ean Pregon Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date SOW W NO. W Section 8 T. 2 SO'R. ILE W.M. 0 Temperature of water 52 Was a chemical analysis made? ☐ Yes The No Bearing and distance from section or subdivision corner (SE 1 of NW 1 & East half of the (12) WELL LOG: So.W. + N.W. of Sec.8 Depth drilled 367 ft. Depth of completed well Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL. FROM Top soil (3) TYPE OF WORK (check): Fine sand & clay, brown New Well Deepening [ Reconditioning | Abandon [7] ndonment, describe material and procedure in Item 11. Gravel cemented Boulders & coarse gravel (4) PROPOSED USE (check): (5) TYPE OF WELL: Gravel fine water br. approx. 95 Driven 🛚 Rotary Domestic 🔀 Industrial 🗌 Municipal 🗎 Clay sandy . brown 105 126 Cable Jetted Irrigation Test Well [ Other Dug Bored Sand fine brown 126 Gravel. cemented (6) CASING INSTALLED: Threaded | Welded X 170 Gravel, medium 190 10 " Diam. from 0 ft. to 287 ft. Gage 330 Gravel, cemented 190 Gravel, cemented w/ water se 220 Gravel, medium .water bearing270 276 Gravel, cemented (7) PERFORATIONS: Perforated? T Yes | No 287 298 Basalt, black 298 L way drive down Type of perforator used Rock, gray , water bearing SIZE of perforations in. by 3/8 Clay, blue 261 perforations from 270 ft. to 281 ft. .280 perforations from 210 ft. to 260 ft. 95 ft. to 105 ft. 2110 perforations from \_\_\_\_ ..... perforations from ..... ..... perforations from ...... ..... ft. to .. Well screen installed Yes No (8) SCREENS: Manufacturer's Name ..... Model No. .... Set from ...... ft. to ..... Diam, Slot size Set from ft, to Work started Dec. 12 19 62 Completed 196 (9) CONSTRUCTION: (13) PUMP: Was well gravel packed? 

Yes No Size of gravel: ..... Manufacturer's Name ..... Gravel placed from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Was a surface seal provided? ★ Yes □ No To what depth? ....27....... ft. Material used in seal- Coment , Sand & Gravel Well Driller's Statement: Did any strata contain unusable water? 

Yes No This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Type of water? Depth of strata Method of sealing strata off NAME Haakon Bottner Drilling Co. (Person, firm, or corporation) (10) WATER LEVELS: Address 11544 N. E. GLISAN ST Static level 180 ft. below land surface Date 2/14/63 Portland 20, OREGON lbs. per square inch Date Artesian pressure Driller's well number ....

License No. ...

March 10 1963

Date ...

Date .....

Log Accepted by:

[Signed] \_\_\_\_\_

(Owner)