

(1) OWNER: Well No. L52970  
 Name MORRIS VAN METER  
 Address 10150 SE 352ND  
 City BORING St OR Zip 97009

(9) LOCATION OF WELL by legal description:  
 County CLACK Lat. ° ' " Long. ° ' "  
 Township 1 S Range 4 E WM.  
 Section 27 SE 1/4 NW 1/4  
 Tax Lot 02100 Lot Block Subdivision  
 Street Address of Well (or nearest Address)  
 10150 SE 352ND AVE BORING, OR 97009

(2) TYPE OF WORK: RECONDITION *Reper*

(3) DRILL METHOD: ROTARY AIR

(4) PROPOSED USE: IRRIGATION

(10) STATIC WATER LEVEL:  
 290 ft. below land surface. Date 05/26/02  
 Artesian pressure \_\_\_\_\_ lb per square in. Date \_\_\_\_\_

(5) BORE HOLE CONSTRUCTION:  
 Special Construction Approval NO Depth of Compl. Well \_\_\_\_\_ ft  
 Explosives used NO Type \_\_\_\_\_ Amount \_\_\_\_\_  
 HOLE SEAL  
 Diam. From To Material From To Amount  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 Seal placement method \_\_\_\_\_  
 Backfill: from \_\_\_\_\_ ft to \_\_\_\_\_ ft Material \_\_\_\_\_  
 Gravel: from \_\_\_\_\_ ft to \_\_\_\_\_ ft Size \_\_\_\_\_

(11) WATER BEARING ZONES:  
 Depth at which water was first found 395  
 From To Est Flow Rate SWL  
 395 422 150 GPM 290  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

(6) CASING/LINER:  
 Diam. From To Gauge Material Connection  
 Casing \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 Liner 6 220 440 .250 STEEL WELDED  
 Final Location of shoe(s) \_\_\_\_\_

(12) WELL LOG:  
 Material Ground elevation \_\_\_\_\_  
 From To SWL  
 DRILLED OUT 6" PVC LINER. DRILLED TO  
 440 FEET. PUT 6" .250 STEEL LINER IN  
 HOLE 220 FEET TO 440 FEET. PERFORATED  
 FROM 300 FEET TO 420 FEET.  
 COARSE CEMENTED GRAVEL 395 408 290  
 FINE BLACK CEMENTED SAND 408 422 290  
 BLUE CLAY 422 440  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
**TED PULLIAM WELL DRILLING**  
**9480 S.E. 172nd**  
**Boring, Oregon 97009**  
**Phone 665-3353**  
 Date started 05/25/02 Completed 05/26/02

(7) PERFORATIONS/SCREENS:  
 Perf. Method TORCH  
 Screens Type \_\_\_\_\_ Material \_\_\_\_\_  
 Slot Tele/pipe  
 From To Size Number Diam. Size Casing/liner  
 420 300 1/8X9 500 6 \_\_\_\_\_ LINER  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to my best knowledge and belief.  
 WWC Number \_\_\_\_\_  
 Signed \_\_\_\_\_ Date \_\_\_\_\_

(8) WELL TESTS: Minimum testing time is 1 hour  
 Test type PUMP  
 Yield GPM Draw-down Drill stem at Time  
 150 1 \_\_\_\_\_ 1 hr.  
 150 1 \_\_\_\_\_ 4 hr  
 \_\_\_\_\_  
 \_\_\_\_\_  
 Temperature of water 51F Depth Artesian Flow Found \_\_\_\_\_  
 Was water analysis done? NO By whom \_\_\_\_\_  
 Reason for water not suitable for use \_\_\_\_\_  
 Depth of strata \_\_\_\_\_

(bonded) Water Well Constructor Certification: I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.  
 WWC Number 616  
 Signed *Ted Pulliam* Date 05/26/02

MAY 28 2002