STATE OF OREGON Water Supply Well Report (as required by ORS 537.765)

Instructions for completing this report are on the last page of this form.

CLAC

Received Date:

Well ID Tag # L

62064

Start Card # 154531

(1) Owner Well Number:	(9) Location of Hole by legal description
Name: MIKE REARDON	County: CLAC Latitude: Longitude:
REARDON NURSERY INC.	Township: 1.00 S Range: 4.00 E
Street: 10050 SE 282ND City: BORING State:OR Zip Code: 97009	Section: 30 NWSW Lot: Block:
(2) Type of Work	Tax Lot: 2501 Subdivision:
New Alter (Recondition) Alter (Repair)	Street Address of Well (or nearest address): 10050 SE 282ND
X Deepening Abandonment	MAP, with location identified, must be attached.
(3) Drill Method	(10) Static Water Level Feet below land surface: 229.0 Date: 02 / 15 / 2003
X Rotary Air Rotary Mud Cable Auger	Artesian Pressure: Date:
Other:	
(4) Proposed Use	(11) Water Bearing Zones Depth at which water was first found: 128.00 ft.
Domestic Community Industrial X Irrigation Injection	From To est Flow swi_
LivestockThermal Other:	128.00 324.00 100.00 128
(5) Bore Hole Construction	360.00 503.00 200.00 229
Special Standards: Depth of completed well: 503.00 ft.	(12) Mol Log Ground Elevation:
Explosives Used: Amount: Type:	(12) Well Log
Hole Seal	Material From To swl
Diameter From To Mtrl From To Sacks/lbs	BASALT-BLACK, HARD 65.00 119.00
12.00 0.00 50.00 BE 0.00 50.00 98	BASALT-BROKEN,BLACK,HARD 119.00 128.00
12.00 50.00 335.00 CE 50.00 335.00 277	CEMENTED GRAVELS,BROWN,SMALL 128.00 324.00 128
8.00 335.00 503.00	CLAY, TAN, BROWN 324.00 358.00 CFMFNTED GRAVELS.LG.BROWN 358.00 420.00 229
	CEMENTED GRAVELS,LG,BROWN 358.00 420.00 229 SAND, RED W/CINDERS 420.00 427.00
How was seal placed? C Other: POURED AND TAMPED	CEMENTED GRAVELS, BROWN 427.00 431.00
Back fill placed from: Material: Filter pack from: Size:	CEMENTED GRAVELS, GRAY 431.00 449.00
	CEMENTED GRAVELS, BROWN 449.00 469.00
(6) Casing / Liner Csnn/ Shoe Shoe	SAND, BLACK 469.00 475.00
Csng/ Snoe Snoe Snoe Liner Diameter From To Gauge Mtrl Weld Thrd at used	CLAY, BROWN WOOD + GRAVEL 475.00 503.00
C 8.00 2.00 -503.00 .250 S X 503 In	
	Note: Extracted all 12" casing.
(7) Perforation / Screens	States decreas the states of the formal decrease decreases.
Perforations: Csng/	TO BEOGIVED
P -360.00 -420.00 0.13 2160 8.00 C AIR PERF.	_
Screens:	1 7 2003
Mtrl From To S Size #Slots Dia. t/pSize Type Gauge	WARE TO STORY SOEPT
	WARE CHARLES DEPT SALLES, CREGON
(8) Well Tests (Minimum testing time is one hour)	
Type Yield Units Drawdown Stem at Duration	Date Started: 01 / 08 / 2003 Date Completed: 02 / 15 / 2003
A 100.00 G 192.00 320.00 1.00	(unbonded) Water Well Constructor Certification:
A 200.00 G 274.00 503.00 1.00	I certify that the work I perform on the construction, alteration, or abandonment of this well is in compliance with Oregon well construction standards. Materials
	used and information reported above are true to the best knowledge and belief.
Temperature of Water: 53 F	Signed by: RONALD SPENGLER WWC #:1585
Was water analysis done? Depth of artesian flow:	(bonded) Water Well Constructor Certification: I accept responsibilty for the construction, alteration, or abandonment work
by whom?	performed on this well during the construction dates reported above. All work
Did any strata contain water unsuitable for use? Too Little Salty	performed during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and belief.
Muddy Odor Colored other:	Signed by: CASEY JONES JR WWC #: 1541
Depth of strata: Page 1	of 1 CASEY JONES WELL DRILLING Phone: 541-747-2806