

RECEIVED

CLAC 60340

AUG 04 2004 Westerberg Drilling, Inc. 36728 S. Kropf Rd. Molalla, OR 97038

STATE OF OREGON

WATER SUPPLY WELL REPORTS SOURCES OF WATER SALEM, OREGON (as required by ORS 537.765)

WELL I.D. # L 67455 START CARD # 166715

Instructions for completing this report are on the last page of this form.

(1) LAND OWNER Well Number Name Leo Gentry Wholesale Nursery Inc. Address PO Box 645 City Gresham State OR Zip 97030

(2) TYPE OF WORK [X] New Well [] Deepening [] Alteration (repair/recondition) [] Abandonment

(3) DRILL METHOD: [X] Rotary Air [] Rotary Mud [X] Cable [] Auger [] Other

(4) PROPOSED USE: [] Domestic [] Community [] Industrial [X] Irrigation [] Thermal [] Injection [] Livestock [] Other

(5) BORE HOLE CONSTRUCTION: Special Construction approval [] Yes [X] No Depth of Completed Well 312 ft. Explosives used [] Yes [X] No Type Amount

Table with columns: HOLE Diameter, From, To, SEAL Material, From, To, Sacks or pounds. Rows include Cement and Bentonite.

How was seal placed: Method [] A [] B [X] C [] D [] E [X] Other Bentonite placed dry. Backfill placed from 312 ft. to 345 ft. Material & pea gravel. Gravel placed from 193 ft. to 312 ft. Size of gravel 6x9 cssi.

(6) CASING/LINER: Table with columns: Diameter, From, To, Gauge, Steel, Plastic, Welded, Threaded. Rows for Casing and Liner.

(7) PERFORATIONS/SCREENS: Table with columns: From, To, Slot size, Number, Diameter, Tele/pipe size, Casing, Liner. Rows for different screen depths.

(8) WELL TESTS: Minimum testing time is 1 hour. Table with columns: Yield gal/min, Drawdown, Drill stem at, Time. Values: 60, 116', 6-hr.

Temperature of water 56° Depth Artesian Flow Found Was a water analysis done? [] Yes By whom NONE Did any strata contain water not suitable for intended use? [] Too little [] Salty [] Muddy [] Odor [] Colored [] Other Depth of strata:

(9) LOCATION OF WELL by legal description: County Clackamas Latitude Longitude Township 5S N or S Range 1E E or W. WM. Section 18 SW 1/4 SE 1/4 Tax Lot 2300 Lot Block Subdivision Street Address of Well (or nearest address) 2nd property N. of 33142 S. Barlow Rd.

(10) STATIC WATER LEVEL: 68 ft. below land surface. Date 7-16-04 Artesian pressure lb. per square inch Date

(11) WATER BEARING ZONES: Table with columns: From, To, Estimated Flow Rate, SWL. Row: 214' to 291' 60 gpm 68'

(12) WELL LOG: Table with columns: Material, From, To, SWL. Rows: soil, clay sandy brown, clay sandy grey, etc.

Date started 6-7-04 Completed 7-21-04

(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. WWC Number Signed Date

(bonded) Water Well Constructor Certification: I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. WWC Number 688 Signed Steve N. Studer Date 7-27-04



36728 S. Kropf Rd., Molalla, OR 97038 • Phone: (503) 829-2526 FAX (503) 829-7514

Westerberg Drilling, Inc.
36728 S. Kropf Rd.
Molalla, OR 97038

Page 2

WELL ID# L 67455

OWNER: Leo Gentry Wholesale Nursery Inc.

ADDRESS: PO Box 645

CITY/STATE/ZIP: Gresham, OR 97030

WELL ADDRESS: 2nd property N. of 33142 S. Barlow Rd.

COUNTY Clackamas TOWNSHIP 5S RANGE 1E

SECTION 18 SW 1/4 SE 1/4 TAX LOT 2300

(11) WATER BEARING ZONES CONT'D FROM PREVIOUS PAGE:

FROM	TO	ESTIMATED FLOW RATE	SWL

(12) WELL LOG INFO. CONT'D FROM PREVIOUS PAGE:

MATERIAL	FROM	TO	SWL
claystone grey & brown	138	155	
siltstone grey & brown	155	159	
claystone blue/green	159	165	
packed silt grey/black	165	171	
clay blue-green	171	175	
clay grey-green	175	188	
packed sand green w/ wood &	188		
claystone		194	
clay blue	194	208	
clay brown	208	214	
sand grey	214	225	
clay grey	225	233	
sand or silt	233	235	
clay grey	235	245	
silt grey	245	260	
clay w/ packed sand	260	279	
sand	279	282	
claystone	282	285	
sand grey fine w/ wood	285	291	
clay blue sticky	291	307	
claystone green	307	320	
clay grey	320	327	
siltstone green	327	345	

6" drive shoe welded on top of 6" riser pipe to facilitate getting inside of riser.

RECEIVED

AUG 04 2004

WATER RESOURCES DEPT
SALEM, OREGON