NOTICE TO WATER WELL CONTRACTOR The original and first copy	L REFERENCE D	1	de	
med with the STATE OF OFFICIAL HERE VALUE AND ANT TE A				
within 30 days from the data				
within 30 days from the date of well completion. C6035 (no not write above the AleEM, OREGON				
			=	
(1) OWNER: \sim	(10) LOCATION OF WELL:	731	7	
Name JIM SOLSO Address RT 3 Box 558	SW 1/4 SE 1/4 Section 22 T. 25 R. 4 E W.M.			
BORING OREGON				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well 🗹 Deepening 🗌 Reconditioning 🗌 Abandon 🗌				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed y	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	75	ft.	
Rotary Diven Cable Jetted Domestic Industrial Municipal	Static level 225.5 ft. below land surface. Date			
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date			
(a) CASING INSTALLED: Threaded				
(5) CASING INSTALLED: Threaded □ Welded ₽ 	(12) WELL LOG: Diameter of well below casing			
6 " Diam. from 270, 5 ft. to 308 ft. Gage, 250"	Depth drilled 308 ft. Depth of completed well 308 ft.			
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
PERFORATIONS: Perforated? Pixes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used TORCIA		1 1	1	
Size of perforations B in. by 1/B in.	MATERIAL TOR South	From To	SWL	
180 perforations from 2.77 ft. to 308 ft.	BROWN CLAY	$\begin{vmatrix} 0 \\ 1 \\ 3 \end{vmatrix}$	· · ·	
perforations from ft. to ft.	RED CLAY	3 21		
perforations from ft. to ft.	BROWN CLAY	21 86	52 3	
(7) SCREENS: Well screen installed?	CLAY AND GRAVEL	86 105	52 5	
(7) SCREENS: Well screen installed? Yes Yoo Manufacturer's Name	SANDY BROWN (LAY	105 118		
Type Model No	CEMENTED (TRAVEL	137 167	179 >	
Diam Slot size Set from ft. to ft.	[15 G.P.M.]	1.1 100		
Diam Slot size Set from ft. to ft.	CLAY AND GRAVEL	137 166		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BROWN CLAY	162 173	G	
Was a pump test made? Ves D No If yes, by whom?	(LAY SOME (TRAVEL SOFT, SANDY BROWN	115 196		
1: 92 gal./min. with 38 ft. drawdown after 24 hrs.	GAY -	196 205		
" " "	(LAY AND GRAVEL	205 218	Š	
	SOFT BLACK SAND-		3	
Bailer test 35 gal./min. with 4 ft. drawdown after / hrs.	STONE (33 G.F.M.	218 242	195	
esian flow g.p.m.	WHITE (LAY	242 255		
perature of water Depth arfesian flow encountered ft.	Work started 1/4 1973 Complet	d 1/27	1973	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1/27	19 7.3	
Well seal-Material usedEMENT	Drilling Machine Operator's Certification:			
Well sealed from land surface to 25	This well was constructed under my direct supervision. Materials used and information reported above are true to my			
Diameter of well bore to bottom of seal in.	best knowledge and belief	above are true	e to my	
Diameter of well bore below seal	[Signed] Klill Date73			
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator) Drilling Machine Operator's License No.	329	•	
Number of sacks of bentonite used in well seal sacks Brand name of bentonite				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Ves 🗌 No Plugs	Name KELLER WELL DRILLING (O.			
Did any strata contain unusable water? 🔲 Yes 🗹 No	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 5365 S.E. HILLWOOD MILWAUKIE			
Method of sealing strata off	[Signed]	1		
Was well gravel packed? Ves \square No Size of gravel: $\frac{3}{B}$ - Gravel placed from 270.5 ft to 308 ft.	Contractor's License No. 462 Date 1		72	
		-/	, 19/	
(USE ADDITIONAL SHEETS IF NECESSARY) SP*45656-119				