

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)

(Do not write above this line)

CLAC
6307

State Well No. 25/4E-2866

State Permit No.

(1) OWNER:
Name ORE-IDA ANNUAL CONFERENCE OF THE UNITED METHODIST CHURCH
Address 1505 SW 18TH AV PORTLAND, OR, 97205

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary Driven Jetted Bored
(4) PROPOSED USE (check): Domestic Industrial Municipal Irrigation Test Well Other

(5) CASING INSTALLED: 6" Diam. from +2 ft. to 57 ft. Gage 250"
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name JOHNSON
Type 5" Model No. 20
Diam. Slot size 20 Set from 57- ft. to 63 ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level.
Is a pump test made? Yes No If yes, by whom? KELLER
Yield: 25 gal./min. with 19 1/2" ft. drawdown after 5 1/2 hrs.
" " " " "
" " " " "
Packer test 20 gal./min. with 12 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Well seal—Material used CEMENT
Well sealed from land surface to 28 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 11 sacks
How was cement grout placed? PUMPED
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County CLACKAMAS Driller's well number 477
NW 1/4 NW 1/4 Section 28 T. 2S R. 4E W.M.
Bearing and distance from section or subdivision corner
1100'S. AND 700'E OF THE NW CORNER OF SEC 28

(11) WATER LEVEL: Completed well.
Depth at which water was first found 55
Static level 25'6" ft. below land surface. Date 8/28/80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 75 ft. Depth of completed well 63 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	1	
BROWN CLAY	1	6	
RED CLAY	6	23	
RED CLAY, SOME DECOMPOSED BOULDERS	23	38	
LOOSE GRAVEL AND SILTY SAND	38	55	
LOOSE SAND AND GRAVEL	55	64	25'6"
CLAY AND GRAVEL	64	68	25'6"
BROWN CLAY	68	75	

Work started 8/22 1980 Completed 8/28 1980
Date well drilling machine moved off of well 8/29 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] C. Kell Date 8/29, 1980
(Drilling Machine Operator)
Drilling Machine Operator's License No. 329

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name KELLER WELL DRILLING CO. (Person, firm or corporation) (Type or print)
Address 6350 SE BROWNLEE, MILWAUKIE
[Signed] C. Kell (Water Well Contractor)
Contractor's License No. 462 Date 8/29, 1980