The original and first copy of this report are to be filed with the E V CAPER WELL REPORTE A C ZS/4E-29ac WATER RESOURCES DEPARTMENT STATE OF OREGON 11979 (Please type or print) SALEM, OREGON 97310 within 30 days from the date State Permit No. 66340 of well completion. WATER RESOURCE SO DEFWEITE above this line) SILEM. UREGUN (1) OWNER: (10) LOCATION OF WELL: Name Thomas A. Poublon County Clackamas Driller's well number 14-79 Address 14680 S. Redland Road, Oregon City, Ore. 14 NE 14 Section 29 T. 28 R. LE 97045 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Eagle Creek / Howlett Road Deepening [Reconditioning [Abandon [] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: | (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven 🖂 Domestic 🖫 Industrial 🗌 Municipal 🗎 Static level ft. below land surface. Date 4-28-79 Cable $\overline{\mathbf{x}}$ Jetted 🖂 Dug Irrigation [Test Well [Other Bored | Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded | (12) WELL LOG: Diameter of well below casing 6 "Diam from +1 ft to 167 ft Gage •250 Depth drilled 190 ft. Depth of completed well 190 5 "Diam from 160 ft to 190 ft Gage .188 Formation: Describe color, texture, grain size and structure of materials; " Diam. from _____ ft. to ____ ft. Gage and show thickness and nature of each stratum and aquifer penetrated. with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? K Yes No. Type of perforator used Mills Knife MATERIAL Size of perforations 1/8 in. by Clay: sticky. orange 14 180 perforations from 115 ft to 160 Clay: tan 37 perforations from Clay: sandy, brown 37 61 perforations from _____ft. to ___ Gravel: cemented 61 10L Clay: brown 10h109 (7) SCREENS: Well screen installed? [] Yes | No Gravel: loose 109 161 Manufacturer's Name Clay: tan 161 168 Clay: sandy. brown 168 176 Diam. Slot size Set from ft. to ft. Clav: brown 176 181 Diam. Slot size Set from 181 Clay: gray 190 Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made?

Yes No If yes, by whom? Yield: gal./min. with ft. drawdown after 35 gal./min. with 18 ft. drawdown after 1 hrs. Bailer test Artesian flow g.p.m. mperature of water 530Depth artesian flow encountered Work started 4-17-19 79 Completed 4-28-Date well drilling machine moved off of well 1-28-(9) CONSTRUCTION: Well seal-Material used Coment grout Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Well sealed from land surface to Materials used and information reported above are true to my best knowledge and belief

[Signed]

[Signed] Diameter of well bore to bottom of seal Diameter of well bore below seal Number of sacks of cement used in well seal ______ 12 ____ sacks Drilling Machine Operator's License No. 398 How was cement grout placed? Pumped through a one inch pipe between the ten inch hole and the six Water Well Contractor's Certification: inch casing to a depth of twenty-two feet. This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? X Yes \(\) No Plugs Size: location ft, Name Steinman Bros. Drilling Co.
(Person, firm or corporation) (Type or print) Did any strata contain unusable water? 🗌 Yes 🕱 No Type of water? depth of strata <u> 23 S. E. Holly Avg., Milw., Ore. 97222</u> Method of sealing strata off Ronald F. McConnell (Water Well Contractor) Was well gravel packed? Nes | No Size of gravel: 3/8 Contractor's License No. 626 Date April 30

NOTICE TO WATER WELL CONTRACTOR