CLAC 63505

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765)

Westerberg Drilling, Inc. 36728 S. Kropf Rd. Molalla, OR 97038

WELL I.D. # L	84747	

START CARD # 191073

nstructions for completing this report are on the last page of this form.		
(1) LAND OWNER Well Number	(9) LOCATION OF WELL (legal County Clackamas	-
Address PO Box 801	Tax Lot 2002	Lot
City Oregon City State OR Zip 97045	Township 4 S	Range 1 E WM
	Tax Lot 2002 Township 4 S F Scction 22 NW	1/4 SW 1/4
2) TYPE OF WORK		(degrees or decimal)
(3) DRILL METHOD		
Z Rotary Air □ Rotary Mud Z Cable □ Auger □ Cable Mud □ Other	Street Address of Well (or nearest addres	
	(10) STATIC WATER LEVEL	
(4) PROPOSED USE ☐ Domestic ☐ Community ☐ Industrial ☑ Irrigation ☐ Thermal ☐ Injection ☐ Livestock ☐ Other	ft. below land surface	
Thermal Injection Livestock Other	ft. below land surface	
(5) BORE HOLE CONSTRUCTION Special Construction: Yes No Depth of Completed Well 422 ft.	Artesian pressure N/A lb. per squa (11) WATER BEARING ZONES	are inch Date
Explosives used: Yes 🚺 No Type Amount	Depth at which water was first found	
BORE HOLE SEAL	From To	Estimated Flow Rate SWL
Diameter From To Material From To Sacks or Pounds	16 20	DNM DNM
16" 0 198 Cement 13 198 163 sacks Bentonite 0 13 47 sacks	290 415	550+ 72'
12 100 722		
How was seal placed: Method		
7 Other Bentonite placed dry	(12) WELL LOG Groun	d Elevation
	Material	
Backfill placed fromft. toft. Material		From To SWL
Gravel placed from 249 ft. to 422 ft. Size of gravel 6-9 & 8-12		1 16
(6) CASING/LINER		16 20
Diameter From To Gauge Steel Plastic Welded Threaded		20 25
and the last last of the second		25 33
	Cemented gravel	33 48
8" riser 248'4" 289'1" .250 🚺 🔲 💆	Clay grey w/ gravel	48 50
Casing: 12" +1 288 .250		50 58
Liner: 8" blank 357'3" 382'4" .250		58 70
8" tail 415'10" 422' .250 🗾 🔲	Packed silt w/ wood grey & green	
Drive Shoe used 🔲 Inside 💋 Outside 🔲 None		75 80
Final location of shoe(s) 288'		80 84
- Hital rocation of shoc(s)		84 86
(7) PERFORATIONS/SCREENS		86 94 94 98
	continued on page 2	34 36
☐ Perforations Method ☑ Screens Type V-wire Material stainless	Date Started 3-21-07 Co	5-15-07
From To Slot Number Diameter Tele/pipe Casing Liner		
Size size	(unbonded) Water Well Constructor C	
0001411 04014111 0414 1011 1011 1011	I certify that the work I performed on	the construction, deepening, alteration, or
2891" 312'6" .055 8" PS	abandonment of this well is in compliance	
382'4" 415'10" .070 8" PS	construction standards. Materials used as the best of my knowledge and belief.	nd information reported above are true to
	are best of my knowledge and benef.	
	WWC Number <u>1768</u>	Date 5-18-07
(8) WELL TESTS: Minimum testing time is 1 hour ✓ Pump ☐ Bailer ☐ Air ☐ Flowing Artesian	Signed Charles	Sum
Yield gal/min Drawdown Drill stem at Time	(bonded) Water Well Constructor Cer	tification
550 132' 1 hr.	I accept responsibility for the constru	
550 153' 4 hr.	abandonment work performed on this we	ell during the construction dates reported
	above. All work performed during this ti	ime is in compliance with Oregon water
Temperature of water 55 Depth Artesian Flow Found	supply well construction standards. This	report is true to the best of my knowledge
	and belief.	
Was a water analysis done? Yes By whom	WWG No. 1 600	D . E40.07
Did any strata contain water not suitable for intended use?	WWC Number 688	Date 5-18-0/
□ Salty □ Muddy □ Odor □ Colored REGEIVED	aim Ati n	Atil.
Depth of strata:	Signed Sum n,	- Casure

CLAC 63505



36728 S. Kropf Rd., Molalla, OR 97038 • Phone: (503) 829-2526 FAX (503) 829-7514

WELL ID#	OWNER/BUSINESS NAME	MAILING ADDRESS	CITY/STATE/ZIP
L84747	Stepping Stones Land, LLC	PO Box 801	Oregon City, OR 97045

WELL ADDRESS	COUNTY	TOWNSHIP	RANGE	SECTION	1/4	1/4	TAX LOT
27977 S. Hwy 170 Canby, OR 97013	Clackamas	48	1E	22	NW	sw	2002

12) WELL LOG INFO. CONTINUED FROM PREVIO MATERIAL	FROM	то	SWL
Cemented gravel	98	100	
Siltstone grey & brown	100	102	
Siltstone softer	102	110	
Siltstone brown & green	110	118	T
Packed sand grey w/ packed silt	118	135	
Clay brown	135	140	
Silt grey	140	150	
Siltstone blue & green	150	171	
Cemented sand & gravel	171	176	
Siltstone grey	176	190	
Silt green soft	190	203	
Siltstone grey	203	205	
Silt green w/ black sand packed	205	208	
Silt grey	208	260	
Silt grey-green	260	290	
Sand grey fine w/ wood layers & clay	290	297	
Sand grey coarse	297	303	
Packed silt grey	303	307	
Sand grey mixed	307	312	
Clay green soft	312	320	
Silt green & grey	320	346	
Sand loose & packed	346	352	
Silt packed	352	355	
Sand grey fine	355	357	
Packed silt green	357	360	
Packed silt grey hard	360	365	
Packed sand green dry	365	375	
Silt grey	375	382	
Sand grey	382	397	
Wood & packed sand	397	402	
Packed sand grey	402	415	
Packed silt grey green	415	422	
Westerberg Drilling, Inc.			

RECEIVED

MAY 2 9 2007 WATER RESOURCES DEPT SALEM, OREGON

Molalia, OR 97038