## STATE OF OREGON WATER SUPPLY WELL REPORT

Westerberg Drilling, Inc. 36728 S. Kropf Rd. Molaila, OR 97038

WELL I.D. # L <u>87</u>	898
START CARD #_1	92907

(as required by ORS 537.765)

Instructions for completing this report are on the last page of this form.	<u> </u>	
(1) LAND OWNER Well Number	(9) LOCATION OF WELL (legal County <u>Clackamas</u>	
Address PO Box 555	Tax Lot _101	Lot
City Molalla State OR Zip 97038	Township 5 S	Range 2 E WM
(2) TYPE OF WORK  New Well	Section 8 NW	1/4 <b>SW</b> 1/4
——————————————————————————————————————	Lat " "or	(degrees or decimal)
Deepening Alteration (repair/recondition) Abandonment Conversion	Long ° "or	(degrees or decimal
(3) DRILL METHOD		
☑ Rotary Air ☐ Rotary Mud ☑ Cable ☐ Auger ☐ Cable Mud	Street Address of Well (or nearest address	
Other		Molalia, OR 97038
(4) PROPOSED USE	(10) STATIC WATER LEVEL	
☐ Domestic ☐ Community ☑ Industrial ☐ Irrigation	168 ft. below land surfa	ce. Date 9-8-07
☐ Thermal ☐ Injection ☐ Livestock ☐ Other		
	ft. below land surfa	
(5) BORE HOLE CONSTRUCTION Special Construction:   Yes  No	Artesian pressure lb. per squa	are inch Date
Depth of Completed Well 355 ft.	(11) WATER BEARING ZONES	
Explosives used: Yes No Type Amount	Depth at which water was first found 78	<b>,</b>
BORE HOLE SEAL	From To	Estimated Flow Rate SWL
Diameter From To Material From To Sacks or Pounds	78   95	10 gpm DNM
16" 0 4 Bentonite 0 2 5 sacks	289 295	25 gpm DNM
12" 4 175 Cement 2 170 97 sacks	308 319	100 gpm 168'
8" 175 355	328 330	15-20 gpm DNM
	337 340	20 gpm DNM
How was seal placed: Method ABBZCDDE	(12) WELL LOG Groun	nd Elevation
☑ Other Bentonite placed dry	1 ` ′	
Backfill placed from 170 ft. to 175 ft. Material sand	Material	From To SWL
Gravel placed from 262 ft. to 355 ft. Size of gravel 8/12 css		0 1 5
(O. CA CINC/LINED		5 23
(6) CASING/LINER Diameter From To Gauge Steel Plastic Welded Threaded	Gravel w/ clay	23 30
		30 40
		40 48
6" 262 282 250	Siltstone grey hard	48 53
5"x6"	Clay grey med	53 78
Liner: bushing 286 287	Packed sand brn w/ siltstone brn Packed silt w/ packed sand blue	78 95 95 102
	Packed silt w/ packed sand blue	102
Orive Shoe used   Inside   Outside   None	Packed sand grey dry	112 115
Final location of shoe(s) cut off @ 355'		115 130
(F) PUR FOR A WAYNESS CREEKING	Clay grey	130 140
(7) PERFORATIONS/SCREENS		140 160
☐ Perforations Method Material stainless	continued on page 2	
••	Date Started 7-26-07 Co	ompleted 9-8-07
From To Slot Number Diameter Tele/pipe Casing Liner	(unbonded) Water Well Constructor (	Contification
Size size 282   287   .045   relief   6"   PS □ □	I certify that the work I performed or	n the construction, deepening, alteration, o
	abandonment of this well is in complian-	ce with Oregon water supply well
288     296     .045     5"     PS		nd information reported above are true to
327 331 .045 5" PS	the best of my knowledge and belief.	
336 341 .045 5" PS	WWC Number	Date
(9) WELL TECTO, Minimum Andrews 1 Language	We Humber	Date
(8) WELL TESTS: Minimum testing time is 1 hour  ☑ Pump ☐ Bailer ☐ Air ☐ Flowing Artesian	Signed	
Yield gal/min Drawdown Drill stem at Time	(bonded) Water Well Constructor Cer	
150 66' A hr.	I accept responsibility for the constru	
	abandonment work performed on this we	ell during the construction dates reported
	above. All work performed during this t	time is in compliance with Oregon water
Temperature of water 58 Depth Artesian Flow Found		s report is true to the best of my knowledge
Was a water analysis done? Yes By whom RECEVED	and belief.	
Did any strata contain water not suitable for intended use?	WWC Number 688	Date 9-12-07
Salty Muddy Odor Colored Other	12	1+.1
Depth of strata: SEP 2 6 2007	Signed Steven 19.	Stable.
		/

## **CLAC 64005**



36728 S. Kropf Rd., Molalla, OR 97038 • Phone: (503) 829-2526 FAX (503) 829-7514

WELL ID#	OWNER/BUSINESS NAME	MAILING ADDRESS	CITY/STATE/ZIP
L87898	Molalla Redi Mix Inc.	PO Box 555	Molalla, OR 97038

WELL ADDRESS	COUNTY	TOWNSHIP	RANGE	SECTION	1/4	1/4	TAX LOT
280 S. Molalla Forest Rd. Molalla, OR 97038	Clackamas	5S	2E	8	NW	sw	101

(12) WELL LOG INFO. CONTINUED FROM PREVIOU	JS PAGE:		
MATERIAL	FROM	то	SWL
Silt grey	160	190	
Packed silt green	190	205	
Packed sand green	205	220	
Silt grey	220	228	
Clay grey & green	228	232	
Silt grey	232	238	
Clay brown	238	244	
Silt grey	244	289	
Packed sand	289	295	
Siltstone green	295	308	
Sand black & green	308	319	
Clay grey	319	321	
Silt green	321	328	
Sand grey	328	330	
Packed silt green	330	337	
Packed sand & wood	337	340	
Silt grey	340	355	
Westerberg Drilling, Inc. 36728 S. Kropf Rd.			
Molaila, OR 97038			
-			

RECEIVED

SEP 26 2007