### STATE OF OREGON

WELL ID # L 94355

WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

Instructions for completing this report are on the last page of this form

503-656-2683

START CARD # W193716

(1) OWNER:	Well Number:	02	(9) LOCATION OF WELL by legal descript	
	ns / David Lawrence		County Clackamas Latitude Township 4SOUTH N or S. Range 2EAST	Longitude E or W. of WM.
Address P.O. Box 736		in 07004		NE 1/4
City Beavercreek	State OR 2	<sup>2</sup> ip <b>97004</b>	Tax lot 00400 Lot Block	Subdivision
(2) TYPE OF WORK:			Street Address of Well (or nearest address) 16350	S. Buckner Creek
X New Well Deepening	g Alteration (repair/recondition	) Abandonment	Rd., Beavercreek, OR	
(3) DRILL METHOD:			(10) STATIC WATER LEVEL: 121 ft. below land surface.	Date 2/6/2008
Rotary Air Rotar	ry Mud Cable	Auger	Artesian pressure lb. per square inc	
(4) PROPOSED USE:			(11) WATER BEARING ZONES:  Depth at which water was first found 43'	
X Domestic Com	· 1i	Irrigation		
Thermal	tion Livestock	Other	From To Estir	nated Flow Rate SWL 10 40
(5) BORE HOLE CON	STRUCTION:		152 163	46 121
Special Construction approva	Yes X No Depth of Com	pleted Well 164 ft.		
Explosives used Yes X		Amount	La company of the com	
HOLE Diameter From To	SEAL Material From To	sacks or pounds	(12) WELL LOG:	
10 0 64 C	Cement & 64	<u> </u>	Ground elevation	
6 64 164 B	Bentonite 0	57 Sacks	Material	From To SWL
			Top soil, brown	
			Clay, red sticky Clay, red sandy	3 24 24 37
			Basalt, gray soft	37 43
How was seal placed: Metho	od   A   X B   C   D	<b>E</b>	Sandstone, multicolor	43 64
Backfill placed from	ft. to ft. Material		Clay, tan w/seams of basalt, gray Sandstone, brown	64 77 77 81
Gravel placed from	ft. to ft. Size of gravel		Sand, brown coarse	81 107
(6) CASING/LINER: Diameter From	To Gauge Steel Plastic	Welded Threaded	Sandstone, brown	107 126
Casing: 8 +1.5	64 .250 X	X	Clay, brown Claystone, brown	126 131 131 148
			Sand, brown coarse	148 152
			Gravel, medium w/seams of sand	152 163 121
Liner: 6 +2	164 .250 X	<b>X</b>	Clay, tan	163 164
		17.	Skyles Drilling, Inc.	
Drive Shoe used X Inside Outside None			1169 Molalla Ave	
Final location of shoe(s) 164	<u>4'.</u>		Oregon City, OR 97045	CEIVED
(7) PERFORATIONS/S	SCREENS:			
	Method Air Perf		Amended #6 JUN	1 6 2000
	Type Material		WATER R	ESOURCES DEPT.
	Number Diameter Size	Casing Liner	SALI	EM, OREGON "
152 163 1/8x1	66	<b>X</b>		
			Date started 1/25/2008 Completed	2/6/2008
		H H	(unbonded) Water Well Constructor Certification	on:
			I certify that the work I performed on the construction, al	
(8) WELL TESTS: Mir	nimum testing time is 1 ho	ur	ment of this well is in compliance with Oregon water supp standards. Materials used and information reported above	•
Pump Bai	ler XAir	Flowing Artesian	knowledge and belief.	are true to the best of my
_			W	WC Number 1884
Yield gal/min Drawd	down Drill stem at	Time		ate 6/11/2008
46	62	1.br	Skýles Drilling, Inc.	
			(bonded) Water Well Constructor Certification: 1 accept responsibility for the construction, alteration, o	
i			performed on this well during the construction dates repor	
Temperature of Water 56.5	1		performed during this time is in compliance with Oregon w	
Was a water analysis done?  Did any strata contain water r		Too little	construction standards. This report is true to the best of n	ny knowledge and belief. WC Number 1592
Salty Muddy Od		, 100 mae		ate 6/11/2008
Depth of strata:			Skyles Drilling, Inc.	4.7200

## STATE OF OREGON

## WA

# **CLAC 64543** INC.

WELL ID # L 94355

START CARD # W193716

WATER SUPPLY WELL REPORT	SKYLES DRILLING	
(as required by ORS 537.765)		

503-656-2683

Instructions for completing this report are on the last page of this form	503-656-2683		
(1) OWNER: Well Number: 02  Name Tammy Stevens / David Lawrence  Address P.O. Box 736	(9) LOCATION OF WELL by legal description:  County Clackamas Latitude Longitude  Township 4SOUTH N or S. Range 2EAST E or W. of WM.  Section 14 NW 1/4 NF 1/4		
City Beavercreek State OR Zip 97004	Section 14 NW 1/4 NE 1/4  Tax lot 00400 Lot Block Subdivision		
(2) TYPE OF WORK:	Street Address of Well (or nearest address) 16350 S. Buckner Creek		
X New Well Deepening Alteration (repair/recondition) Abandonmen	nt Rd., Beavercreek, OR		
(3) DRILL METHOD:	(10) STATIC WATER LEVEL:		
X Rotary Air	121 ft. below land surface. Date 2/6/2008 Artesian pressure lb. per square inch. Date		
(4) PROPOSED USE:	(11) WATER BEARING ZONES:  Depth at which water was first found 43'		
X Domestic   Community   Industrial   Irrigation			
Thermal Injection Livestock Other	From To Estimated Flow Rate SWL 43 64 10 40		
(5) BORE HOLE CONSTRUCTION:	152 163 46 121		
Special Construction approval Yes XNo Depth of Completed Well 164			
Explosives used Yes X No Type Amount HOLE SEAL Amount			
Diameter From To Material From To sacks or pounds 10 0 64 Cement & 64	(12) WELL LOG:  Ground elevation		
6 64 164 Bentonite 0 57 Sacks	Material From To SWL		
	Top soil, brown 0 3 Clay, red sticky 3 24		
	Clay, red sticky 3 24 Clay, red sandy 24 37		
How was seal placed: Method   A   X B   C   D   E	Basalt, gray soft 37 43		
Other	Sandstone, multicolor 43 64 Clay, tan w/seams of basalt, gray 64 77		
Backfill placed from ft. to ft. Material	Sandstone, brown 77 81		
Gravel placed from ft. to ft. Size of gravel	Sand, brown coarse 81 107		
(6) CASING/LINER:	Sandstone, brown 107 126		
Diameter From To Gauge Steel Plastic Welded Thread Casing: 8 +1.5 64 .250 X X	Clay, DiOWII		
6 +2 164 .250 X	Claystone, brown 131 148 Sand, brown coarse 148 152		
	Gravel, medium w/seams of sand 152 163 121		
Liner: None	Clay, tan 163 164		
Drive Shoe used X Inside Outside None	Skyles Drilling, Inc. 1169 Molalla Ave.		
Final location of shoe(s) 164'	Oregon City, OR 97045 RECEIVED		
(7) PERFORATIONS/SCREENS:	(503) 656-2683		
X Perforations Method Air Perf	MAR 0 3 2008		
Screens Type Material	WATER RESOURCES DESC		
Slot Tele/pipe From To size Number Diameter size Casing Liner	WATER RESOURCES DEPT SALEM, OREGON		
152 163 1/8x1 66	OALEW, OREGON		
	Date started 1/25/2008 Completed 2/6/2008		
	(unbonded) Water Well Constructor Certification:		
	I certify that the work I performed on the construction, alteration, or abandon-		
(8) WELL TESTS: Minimum testing time is 1 hour	ment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my		
Pump Bailer X Air Flowing Artesian	,		
( ) to my	WWC Number 1884		
Yield gal/min Drawdown Drill stem at Time	Signed Date 2/7/08		
46 62 1 hr.	Skyles Drilling, Inc.		
	(bonded) Water Well Constructor Certification:		
	I accept responsibility for the construction, alteration, or abandonment work		
Temperature of Water 56.5 Depth Artesian Flow found	performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well		
Was a water analysis done? Yes By whom	construction standards. This report is true to the best of my knowledge and belief.		
Did any strata contain water not suitable for intended use?	WWC Number 1592		
Salty Muddy Odor Colored Other	Signed Street Chause Date 2/7/08		
Depth of strata:	Skyles Drilling, Inc.		