NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
JAN 27 1975
STATE ENGINEER
SALEM, OREGON

CLAC NC 6519

WATER WELL REPORT
STATE OF OREGON (Please type or print) (Do not write above this line)

State Well No. 25/4E-32dd
State Permit No.

(1) OWNER:
Name Tom BARKER
Address RT 1 Box 225-FF EAGLE CREEK

(2) TYPE OF WORK (check):
New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):
Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:
Threaded [] Welded [X]
6 " Diam. from 0 ft. to 48 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? [] Yes [X] No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 12 gal./min. with 10 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water 51 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT
Well sealed from land surface to 30 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 5 sacks
Number of sacks of bentonite used in well seal — sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water — lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County CLACKAMAS Driller's well number
SE ¼ SE ¼ Section 32 T. 2S R. 4E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 15 ft.
Static level 21 ft. below land surface. Date 11/10/74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 48 ft. Depth of completed well 48 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
SOIL	0	2	
BROWN CLAY & BOULDERS	2	21	
CEMENTED GRAVEL	21	48	21

Work started 10/5 1974 Completed 11/10 1974
Date well drilling machine moved off of well 11/10 1974

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Wallace Haarsland Date 1/24, 1975
(Drilling Machine Operator)
Drilling Machine Operator's License No. 380

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name GAARSLAND DRILLING CO
(Person, firm or corporation) (Type or print)
Address P.O. Box 31 EAGLE CREEK 97022
[Signed] Wallace L Gaarsland
(Water Well Contractor)
Contractor's License No. 543 Date 1/24, 1975

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119