

The original and first copy of this report are to be filed with the

RECEIVED JUN 7 - 1971

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310

STATE OF OREGON

State Well No. 2/5-17 ca

within 30 days from the date of well completion.

(Please type or print)

State Permit No.

STATE ENGINEER SALEM, OREGON

(Do not write above this line)

66819 CLAC

(1) OWNER:

Name Oral Hull Foundation
Address P. O. Box 157, Sandy, Or. 97055

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED:

6" Diam. from 0 ft. to 82 ft. Gage 0.250
Threaded [ ] Welded [X]

PERFORATIONS:

Perforated? [ ] Yes [X] No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No

Manufacturer's Name

Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [ ] Yes [X] No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

Bailer test 10 gal./min. with Total drawdown after 2 hrs.
Artesian flow g.p.m.

Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement grout and puddled clay
Well sealed from land surface to 82 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 7 sacks
Number of sacks of bentonite used in well seal --- sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [X] Yes [ ] No plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 32-71
SW 1/4 NE 1/4 Section 17 T. 2S R. 5E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 180 ft.
Static level 64 ft. below land surface. Date 5/22/71
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 220 ft. Depth of completed well 190 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Clay, brown; Cement gravel and boulders; Brown sandstone; Eagle Creek formation; Soft brown conglomerate; Soft green conglomerate.

Work started April 27 19 71 Completed May 22 19 71
Date well drilling machine moved off of well May 28 19 71

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Jack Dues Date June 3, 19 71
(Drilling Machine Operator)

Drilling Machine Operator's License No. 67

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Steinman Bros.
(Person, firm or corporation) (Type or print)

Address 14912 S.E. Kellogg Ave., Milwaukie, Or. 97222

[Signed] Robert E. McConnell
(Water Well Contractor)

Contractor's License No. I Date June 3, 19 71