CLAC 69797

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

WELL LABEL # L	
START CARD#	209799

(1) LAND OWNER Owner Well 1.D.	(O) LOCATION OF WELL (Local Local description)
	(9) LOCATION OF WELL (legal description)
First Name Last Name	County CLACKAM Twp 3 S N/S Range 1 E E/W WM
Company LITTLE PRINCE OF OREGON NURSERY	Sec 19 SW 1/4 of the NW 1/4 Tax Lot 307
Address 15868 NE EILERS RD.	Tax Map Number Lot
City AURORA State OR Zip 97002	Lat O O O O O O O O O O O O O O O O O O O
(2) TYPE OF WORK New Well Deepening Conversion	Long DMS of DD
Alteration (repair/recondition) X Abandonment	Street address of well Nearest address
	15868 NE EILERS RD.
(3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud	
	(10) STATIC WATER LEVEL
Reverse Rotary Other	Date SWL(psi) + SWL(ft)
(4) PROPOSED USE Domestic X Irrigation Community	Existing Well / Predeepening Completed Well
Industrial/Commercial Livestock Dewatering	Flowing Artesian? Dry Hole?
Thermal Injection Other	
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy)	WATER PLANT BY OWN ON BY OWN OWN ON BY OWN OWN ON BY OWN
Depth of Completed Well 0 ft.	SWL Date From To Est Flow SWL(psi) + SWL(ft)
BORE HOLE SEAL sacks/	7/2013
Dia From To Material From To Amt Ibs	
6.25 0 309 Cement 0 309 43 S	
	SALEM OR
	(11) WELL LOC
	Glound Elevation
How was seal placed: Method A B C D E	Material From To
Other PUMPED INTO WELL B	TOPSOIL 0 1
Backfill placed from ft. to ft. Material	FINE BROWN SAND 13 33
Filter pack from ft. to ft. Material Size	FINE TO COARSE BROWN SAND 33 39
Explosives used: Yes Type Amount	FIRM GRAY SANDY CLAY 39 61
(6) CASING/LINER	STICKY BLUE GRAY CLAY 61 66
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	FINE TO MEDIUM BLACK SAND 66 69
	STICKY BLUE GRAY CLAY 69 87
	STICKY BROWN CLAY 87 105
	STICKY BLUE GRAY CLAY
	FINE COMPACT GRAY SAND 150 155
	FIRM DARK GRAY CLAYSTONE 155 178
ShoeOutsideOther Location of shoe(s)	STICKY GRAY CLAY 178 199
Temp casing Yes Dia From To	SOFT GRAY SANDY CLAY 199 218
(7) PERFORATIONS/SCREENS	STICKY GRAY CLAY 218 309
Perforations Method	DRY HOLE ABANDONED:
Screens Type Material	PUMPED CEMENT GROUT INTO WELL BORE 309 0
Perf/S Casing/Screen Som/slot Slot # of Tele/	
creen Liner Dia From To width length slots pipe size	Date Started 06-10-2013 Completed 06-13-2013
	(unbonded) Water Well Constructor Certification
	I certify that the work I performed on the construction, deepening, alteration, or
	abandonment of this well is in compliance with Oregon water supply well
	construction standards. Materials used and information reported above are true to the best of my knowledge and belief.
(9) WELL TECTS AS:	
(8) WELL TESTS: Minimum testing time is 1 hour	License Number Date Password : (if filing electronically)
Pump Bailer Air Flowing Artesian	Signed
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	
	(bonded) Water Well Constructor Certification
	I accept responsibility for the construction, deepening, alteration, or abandonment
Temperature °F Lab analysis Yes By	work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well
	construction standards. This report is true to the best of my knowledge and belief.
Water quality concerns? See (describe below) From To Description Amount Units	
	License Number 1266 Date 06-13-2013 Password: (if filing electronically)
	Signed Signed
	Signed Contact Info (optional)