

filed with the STATE ENGINEER, SALEM, OREGON 97310

State Well No. 1/3-31 C

within 30 days from the date of well completion.	ype or print) State Permit No	State Permit No.		
(1) OWNER: CREGON	(11) WELL TESTS: Drawdown is amount water level is lowered below static level			
Name LELAND D. WHEELER	Was a pump test made? ☐ Yes No If yes, by who	_		
Address 1940 S.E. 181	Yield: gal./min. with ft. drawdo		hrs.	
PORTLAND OREGON	n n		"	
(2) LOCATION OF WELL:	n n n		"	
	Bailer test 36 gal./min. with 35 ft. drawd	own after	hrs.	
County CLACKAMAS Driller's well number 23	Artesian flow g.p.m. Date			
NE 14 NW 14 Section 3 T. IS R3E W.M.	Temperature of water 56 Was a chemical analysis	made? 🗌 Yes	X No	
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below c	asing		
- 1AX LOT 18-1-1		97-	, ,	
A second	Depth drilled 227 ft. Depth of completed we		a and	
	Formation: Describe by color, character, size of materishow thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	the material in	each	
, the state of the	stratum penetratea, with at least one entry for each c	Thursday of John		
	MATERIAL	FROM 1		
(3) TYPE OF WORK (check):	TOP SOIL	0 3		
Well 🕻 Deepening 🗌 Reconditioning 🛭 Abandon 🗆	RROWN CLAY	3 5	50	
abandonment, describe material and procedure in Item 12.	REO CLAY	50 3	<u>55</u>	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	WEATHERED LAVA	55 (<u>60</u>	
Rotary D Driven D	ROCK SOFT GRAY	60 6	<u> </u>	
Domestic Industrial ☐ Municipal ☐ Cable I Jetted ☐ Irrigation ☐ Test Well ☐ Other ☐	ROCK BROKEN HARD	87 9	<u>8</u>	
Dug Bored	BOCK SOPT GRAY	98 1	<u> </u>	
(6) CASING INSTALLED: Threaded Welded	ROCK SOFT KED	130 1	30	
6, "Diam from 6 ft to 209 ft. Gage : 250	KOCK SOFT, GRAY	130 1	<u>ာ့ ဗ</u>	
59/16" Diam. from 209 ft. to 227 ft. Gage 10		132 1	<u> 600</u>	
"Diam. fromft. toft. Gage	LOCK SOFT (SLAY	160	40	
(7) PERFORATIONS: Perforated? A Yes No	ROCK, HAKO, CKAY	100	22	
	ROCK SOFT BROWN	190	~	
Type of perforator used	BUE CLAY	100 9	0	
Size of perforations /8 in. by 6 in.	BROWN CLMY	205 2	15	
		215		
perforations from				
perforations fromft. toft perforations fromft. toft			 	
perforations from ft. to ft		1		
		1 .		
(8) SCREENS: Well screen installed? ☐ Yes No				
Manufacturer's Name	•			
jeModel No				
Diam, Slot size Set from ft. to ft.	work started 1 - Completed	4-25	19 6	
Diam Slot size Set from ft. to ft	Date well drilling machine moved off of well	-25	19 E	
(9) CONSTRUCTION:	(13) PUMP:			
Well seel. Meterial used in seel. CENENT	Manufacturer's Name			
Well seal—Material used in sealft. Was a packer used?	. Manuacturer & Hanne			
	Type:	H.P		
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:			
Was a drive shap words of Yes II No.	This well was drilled under my jurisdiction	and this ren	ort i	
Was well gravel packed? May Yes □ No Size of gravel: 14 To 8	true to the best of my knowledge and belief.	arra arra reb	J. () 1;	
Gravel placed from 80 ft. to 210 ft.	NAME KELLEY WAS DOLL	1 2240		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (T	ype or print)		
Type of water? depth of strata	Address 16306 S.E. FRANKLIN	Y YORT	CLA	
Method of sealing strata off	-	2 70		
	Drilling Machine Operator's License No.	24]		
(10) WATER LEVELS:	Signed] COKOLL	- Comment		
Static level 04 ft. below land surface Date 4-25-6	(Water Well Contractor	•		
Artesian pressure lbs. per square inch Date	Contractor's License No 462 Date 4-	30 1	. 6	

(USE ADDITIONAL SHEETS IF NECESSARY)