

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED

JUL 17 1970

STATE OF OREGON WATER WELL REPORT

STATE OF OREGON

(Please type or print)

Write above this line

STATE ENGINEER SALEM, OREGON

State Well No. 2/6-22 db

07402 CLAC

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

(1) OWNER:

Name Byron H. Sweeney
Address 6632 N. E. Wygant, Portland, Or. 97218

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

CASING INSTALLED:

10" Diam. from 0 ft. to 111'8" ft. Gage 0.250
Threaded [] Welded [X]
Motel

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Bailer test 60 gal./min. with 20 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water 50 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal-Material used Bentonite and drill cuttings
Well sealed from land surface to 45 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 3 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 35-70
NW 1/4 SE 1/4 Section 22 T. 2S R. 6E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 53 ft.
Static level 79 ft. below land surface. Date 7-10-70
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10
Depth drilled 118 ft. Depth of completed well 118 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Clay, yellow; Peat bog, brown; Clay, grey, gritty; Clay, gravel and boulders; Clay, grey, sandy; Gravel & sand, loosely cemented (water); Rock, Rhododendron.

Work started June 29 1970 Completed July 10 1970
Date well drilling machine moved off of well July 12 1970

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Robert E. McConnell Date July 14, 1970
(Drilling Machine Operator)

Drilling Machine Operator's License No. 68

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Steinman Bros.
(Person, firm or corporation) (Type or print)

Address 14912 S.E. Kellogg, Milwaukie, Or. 97222

[Signed] Robert E. McConnell
(Water Well Contractor)

Contractor's License No. I Date July 14, 1970