## STATE OF OREGON

JIIN 1 2 1984

25/IDF-21, al

WATER WELL REPORT (as required by ORS 537.765)

PLEASE TYPE of PRINTING RESOURCES DEPT SALEM, OREGON

	\$ <del></del>

(for official use only)

(1) OWNER: (10) LOCATION OF WELL by legal description: Clackamas SE<sub>1/4</sub> NE 1/4 of Section 26 COUNTRY CLUB WATER DISTRICT County 2 South 6 East P.O. BOX 168 Township (Township is North or South) (Range is East or West) BRIGHTWOOD OREGON City P.O. BOX 168, (2) TYPE OF WORK (check): MAILING ADDRESS OF WELL (or nearest address) Brightwood, Oregon 97011 New Well Deepening Reconditioning Abandon [ If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL of COMPLETED WELL: (3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Air A Driven П Industrial ☐ Municipal Depth at which water was first found Domestic **X**1 Thermal: Static level 120 ft. below land surface. Date 6-5-84 Rotary Mud Withdrawal ☐ Reinjection Irrigation Other: Artesian pressure lbs. per square inch. Date П ☐ Grounding Bored Piezometric (12) WELL LOG: Diameter of well below casing .... (5) CASING INSTALLED: Steel Depth drilled ft. Depth of completed well 280 Plastic 귳 Threaded Welded Formation: Describe color, texture, grain size and structure of materials; and show thickness +2 ...." Diam. from ... and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal ...." Diam. from ...... ft. to ...... Gauge water-bearing strata. LINER INSTALLED: Plastic MATERIAL From Gauge 160# PVC То ft. to . 280 Soil 0 3 ... ft. Clay, brown 3 8 (6) PERFORATIONS: Perforated? Clay, brown & boulders 8 52 Size of perforations in. Basalt, broken 52 57 240 ft. to . 275 ft. ... perforations from . Basalt, black 57 66 ft to perforations from Basalt, black broken 66 76 ... perforations from ..... Basalt, black 76 155 Basalt, red (7) SCREENS: 155 162 Well screen installed? 

Yes No Basalt, black 162 168 Manufacturer's Name ..... Basalt, black, crevised 168 189 Type ...... Basalt, black, softer 189 236 Basalt, grey 236 244 Slot Size ..... Set from ...... Basalt, black 244 247 Drawdown is amount water level is lowered (8) WELL TESTS: below static level Basalt, black, 247 fractured 20 277 Basalt, black Was a pump test made? Yes No If yes, by whom? 277 gal./min. with ft. drawdown after hrs, 23 gpm w/drill stem @ 262' 11 gal./min. with drill stem at 212 ft. Air test 1 hrs. Bailer test gal./min. with ft. drawdown after hrs. Artesian flow nperature of water Depth artesian flow encountered ..... 5-29-84 Date work started \_\_ /completed (9) CONSTRUCTION: Special standards: Yes I No IX Date well drilling machine moved off of well Cement w/5% Bentonite Well seal-Material used .... (unbonded) Water Well Constructor Certification (if applicable): 30 Well sealed from land surface to This well was constructed under my direct supervision. Materials used and 10 in. Diameter of well bore to bottom of seal information reported above are true to my best knowledge and belief. Diameter of well bore below seal ... 12 sacks 🗷 pounds 🗆 [Signed] ..... Amount of sealing material .. Pumped How was cement grout placed? ..... (bonded) Water Well Constructor Certification:
Bond 94-97-459 Issued by: Fidelity & Deposit Co mber) (Surety Company Name) Marvin D. Skyles (SKYLES DRILLING) (number) No On behalf of Was pump installed? ... Туре ...... НР .... (type or print name of Water Well Constructor) Plugs ... Was a drive shoe used? Yes \( \simega \) No License #553 ☐ Yes ※ No Did any strata contain unusable water? This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief: Type of Water? depth of strata Method of sealing strata off (Signed) . Was well gravel packed? 

Yes X No Size of gravel: 05 June 1984 Gravel placed from .... NOTICE TO WATER WELL CONSTRUCTOR WATER RESOURCES DEPARTMENT,