STATE OF OREGON

CLAC 74813

WELL ID#L	12964
-----------	-------

(S DRILLING, INC. START CARD# <u>W1042005</u> 503-656-2683 CLACA - 74813
(1) OWNER: Well Number: 01	(9) LOCATION OF WELL by legal description:
Name Sebastian Stalman	County Clackamas Latitude Longitude
Address 22400 S Stormer Rd	Township <u>3SOUTH</u> N or S. Range <u>3EAST</u> E or W. of WM. Section <u>14</u> <u>SE</u> <u>1/4</u> <u>NW</u> 1/4
City Estacada State OR Zip 97023	Tax lot 00802 Lot Block Subdivision
(2) TYPE OF WORK: X New Well Deepening Alteration (repair/recondition) Abandonn	Street Address of Well (or nearest address) 22400 S Stormer Rd.
X New Well ☐ Deepening ☐ Alteration (repair/recondition) ☐ Abandonn	(10) STATIC WATER LEVEL:
(3) DRILL METHOD: X Rotary Air	0.5 ft. below land surface. Date 2/14/2019 Artesian pressure lb. per square inch. Date
X Other Holte	(11) WATER BEARING ZONES:
(4) PROPOSED USE:	Depth at which water was first found 20'
▼ Domestic	Zo
Thermal Injection Livestock Other	From To Estimated Flow Rate SWL
(5) BORE HOLE CONSTRUCTION:	20 57 12 0.5
Special Construction approval Yes No Depth of Completed Well 58 Explosives used Yes No Type Amount	
HOLE SEAL Amount Diameter From To Material From To sacks or poun	(/42) WELL LOG:
10 0 20 Bentonite 20 0 12 Sacks 7.6 20 58	Marie Francisco
Calculated 9 Sacks	Material From To SWL
	Clay, brown 1 4
	Lava, multicolored soft 4 10
	Conglomerate, multicolored 10 20
How was seal placed: Method A B C D E	Gravel, multicolored cemented 20 57 0.5
X Other Poured bentonite Backfill placed from ft. to ft. Material	Clay, tan sandy 57 58
Gravel placed from ft. to ft. Size of gravel	
(6) CASING/LINER:	
Diameter From To Gauge Steel Plastic Welded Three	aded
Casing: 6 +2.5 56.5 .250 🖾 🗆 🔯	
	SKYLES DRILLING, INC.
Liner: None	
	_
Drive Shoe used ☐ Inside ☐ Outside ☒ None Final location of shoe(s)	RECEIVED
(7) PERFORATIONS/SCREENS:	
Perforations Method	FEB 2 5 2019
Screens Type Material	
Slot Tele/pipe	OWRD
From To size Number Diameter size Casing Line	
None	
	ment of this well is in compliance with Oregon water supply well construction
(8) WELL TESTS: Minimum testing time is 1 hour	standards. Materials used and information reported above are true to the best of my
Pump Bailer XAir Flowing Artesi	knowledge and belief WWC Number 1715
Yield gal/min Drawdown Drill stem at Time	Signed Date 2/19/2019
12 55 1 hr.	Skyles Drilling, Inc.
	(bonded) Water Well Constructor Certification:
	l accept responsibility for the construction, alteration, or abandonment work
TDS Amount 42 ppm	performed on this well during the construction dates reported above. All work
Temperature of Water 59° Depth Artesian Flow found Was a water analysis done? X Yes By whom SDI, Iron 0.75 ppm	performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.
Was a water analysis done? X Yes By whom SDI, Iron 0.75 ppm Did any strata contain water not suitable for intended use?	WWC Number 2006

ORIGINAL - WATER RESOURCES DEPARTMENT

Salty Muddy Odor Colored Other

Depth of strata:

FIRST COPY - CONSTRUCTOR

Signed

SECOND COPY - CUSTOMER

Skyles Drilling, Inc.

Date 2/19/2019