STATE OF OREGON WATER SUPPLY WELL REPORT **CLAC 75420**

Page 1 of 1 WELL I.D. LABEL# L 132925 START CARD# 1045090

(as required by ORS 537.765 & OAR 690-205-0210)	11/25/	/2019 ORIGINAL LOG #		
(1) LAND OWNER Owner Well I.D.				
First Name Last Name		(9) LOCATION OF WELL (legal descri	intion)	
Company TREES NW	_	County CLACKAMAS Twp 1.00 S N/S I	_	E/W WN
Address 9720 SE 362ND AVE		Sec <u>27 NE 1/4 of the SE 1/4</u>		
City BORING State OR Zip 97009	_	Tay Man Number	Lot	<u> </u>
(2) TYPE OF WORK New Well Deepening Conversi	ion	Let ° ' "Or		DMS or DD
Alteration (complete 2a & 10) Abandonment(comp	lete 5a)	Tax Map Number Lat' " or Long ' " or Street address of well Nearest a		DMS or DD
(2a) PRE-ALTERATION Dia + From To Gauge Stl Plstc Wld Thrd		Street address of well Nearest a	ddress	DIVIS OF DD
Casing:		9720 SE 362ND AVE. BORING, OR 97009		
Material From To Amt sacks/lbs				
Seal:	ŀ			
(3) DRILL METHOD	— I	(10) STATIC WATER LEVEL		
Rotary Air Rotary Mud Cable Auger Cable Mud		Existing Well / Pre-Alteration Date S	WL(psi) +	SWL(ft)
Reverse Rotary Other		Completed Well 10/30/2019	+	303
(4) PROPOSED USE Domestic X Irrigation Community			ry Hole?	303
Industrial/ Commercial Livestock Dewatering		WATER BEARING ZONES Depth water wa	· Ш	01.00
Thermal Injection Other		*		
			SWL(psi) +	SWL(II)
(5) BORE HOLE CONSTRUCTION Special Standard (Atta	ich copy)	10/30/2019 401 482 200		303
Depth of Completed Well 482.00 ft.			<u> </u>	
BORE HOLE SEAL Dia From To Material From To Amt	sacks/		 	
	lbs S			
10 263 482 Calculated 71.54			⊥ ∟	
		(11) WELL LOG Ground Flevation		
Calculated	_	Ground Elevation		
How was seal placed: Method A B XC D	3	Material	From	To
Other		Sticky brown clay	0	56
Backfill placed from ft. to ft. Material		Multicolored cemented gravel Grey cemented gravel	56 121	212
Filter pack from ft. to ft. Material Size		Grey medium hard basalt	212	263
Explosives used: Yes Type Amount		Brown small gravel w/ sand	263	346
(5a) ABANDONMENT USING UNHYDRATED BENTONITE]	Brown sand w/ brown gravel	346	401
Proposed Amount Actual Amount		Medium multicolored gravel	401	455
(6) CASING/LINER		Course black sand	455	465
Casing Liner Dia + From To Gauge Stl Plstc Wlo		Medium multicolored gravel Heaving brown sand	465 471	471 482
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	<u> </u>	rieaving brown sand	4/1	402
● 8 □ 263 482 .250 ▼ X	↓ J			
	₁ -			
	1 H∣			
Shoe Inside Outside Other Location of shoe(s) 482	ıШ		++	
<u> </u>	—		 	
Temp casing Yes Dia From + To			 	
(7) PERFORATIONS/SCREENS Perforations Method Air knife				
		Data Stanta 110/7/2010 Campleton	1 10/20/2010	
Screens Type Material Perf/ Casing/ Screen Scrn/slot Slot # of	Tele/	Date Started 10/7/2019 Complete	d 10/30/2019	
	ipe size	(unbonded) Water Well Constructor Certification		
Perf Casing 8 400 440 .125 2 350		I certify that the work I performed on the construc		
		abandonment of this well is in compliance with		
		construction standards. Materials used and informa the best of my knowledge and belief.	non reported ab	ove are true to
			11/25/2019	
(O) WELL TECTS M		1/38 Date	.1/25/2019	
(8) WELL TESTS: Minimum testing time is 1 hour		Signed VANCE WAGNER (E-filed)		
Pump Bailer • Air Flowing Artes	sian			
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)		(bonded) Water Well Constructor Certification		
200 482 1.5		I accept responsibility for the construction, deepen work performed on this well during the construction		
		performed during this time is in compliance with		
Temperature 54 °F Lab analysis Yes By		construction standards. This report is true to the best		
	ppm	License Number 1738 Date 11.		
	nits		23/2017	
	$ \mid$ \mid	Contact Info (optional)		
ODICINAL WATER RECOL	LID CEC D	ED A D'IMENIT		