NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

_	STATE OF OREGINEER	
نځ	Please type or pring TATE SUGINEER 7580 not write above this line ALEM. OREGON rmit No.	

(1) OWNER:	(11) LOCATION OF WELL:			
Name Brown Enterprises (Timberline Rim)	County Clackimas Driller's well m	ımber		
Address 847 N.E. 110 Seattle, Wishington	NE 14 NE 14 Section 30 T. 2	S R.	7 E	W.M.
	Bearing and distance from section or subdivisio	n corner		
(2) TYPE OF WORK (check):				
New Well (12 Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.			,	
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Driven Domestic Industrial Municipal M	(12) WELL LOG: Diameter of well			
Cable	Depth drilled 486 ft. Depth of compl			
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and struc	ture of m	aterials;
CASING INSTALLED: Threaded Welded	with at least one entry for each change of form	nation. Re	eport each	change
8" Diam. from	in position of Static Water Level as drilling pro	oceeds. N	ote drillir	ng rates.
16" Diam. from 0 ft. to 25 ft. Gage 25	MATERIAL	From	То	SWL
	Clay brown a Bodders	Ø	25	
PERFORATIONS: Perforated? Yes No. Type of perforator used	Basalt broken	25	93	
Size of perforations in. by in.	Basalt black	93	118	-
perforations from ft. to ft.				
perforations from ft. to ft.	Lava Grey	118	290	
perforations from ft. to ft.				
perforations from ft. to ft.	Lava gray hard	290	34/	
perforations from ft. to ft.		<u> </u>		
(7) SCREENS: Well screen installed? Yes No	Lava grey	341	379	
Manufacturer's Name	Basalt black	379	385	
Type				
Diam. Slot size Set from ft. to ft.	Lauz grey	385	469	
Diam Slot size Set from ft. to ft.				
(8) WATER LEVEL: Completed well.	Lave grey porous	469	482.	27
Static level 27 ft. below land surface Date Nov 14,68		-		
A lan pressure lbs. per square inch Date	have grey	482	486	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes No If yes, by whom?		<u> </u>		
Yield: 122 gal./min. with 61 ft. drawdown after 24 hrs.	Work started Sap 3 C 19 68 Completed Nov. 20 1968			
" " "	Date well drilling machine moved off of well	now	-20	1968
" " " "	Drilling Machine Operator's Certification:			
	This well was constructed under my d	lirect sup		
Bailer test gal./min. with ft. drawdown after hrs.	rials used and information reported about knowledge and belief.	ve are 1	rue to r	ny best
Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? ★ Yes □ No	[Signed Marie A Shyles Date Mar 18, 1968			
	(Drilling Machine Operator)		_	
(10) CONSTRUCTION: Well seal-Material used Coment	Drilling Machine Operator's License No.		24	
Well seal—Material used Cemont Depth of seal	Water Well Contractor's Certification:	-		
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisd	liction a	nd this r	eport is
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and bel		, <u>`</u>	,
Was a drive shoe used? Yes No	NAME (Person, firm or corporation)	M.Z.	e or print)	pply
Did any strata contain unusable water? Yes No	C) ada tone (7	On.	/
Type of water? depth of strata	Address 7000		. <u> </u>	
Method of sealing strata off	[Signed Leavel Th.	LEIS	Res	
Was well gravel packed? ☐ Yes 🕱 No Size of gravel:	(Water Well Contra	actor)		
Gravel placed fromft. toft.	Contractor's License No. 55 Date	12/-	6	19.68
Graver placed Hour	,			