

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED

ca

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER SALEM, OREGON

State Well No. 25/7E-32

State Permit No.

CLAC  
7631

DEC 6 1973

(1) OWNER:

Name WHISTLE STOP TAVERN  
Address WEAVER CREEK

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Driven   
Cable  Jetted   
Dug  Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

(5) CASING INSTALLED:

Threaded  Welded   
8" Diam. from 0 ft. to 87 ft. Gage 350  
5" Diam. from 0 ft. to 126 ft. Gage 188

(6) PERFORATIONS:

Perforated?  Yes  No  
Type of perforator used TORON  
Size of perforations 1/4 in. by 10 in.  
35 perforations from 85 ft. to 110 ft.

(7) SCREENS:

Well screen installed?  Yes  No  
Manufacturer's Name \_\_\_\_\_ Model No. \_\_\_\_\_  
Type \_\_\_\_\_ Diam. \_\_\_\_\_ Slot size \_\_\_\_\_ Set from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom?  
Yield: 15 gal./min. with 20 ft. drawdown after 4 hrs.  
Bailer test \_\_\_\_\_ gal./min. with \_\_\_\_\_ ft. drawdown after \_\_\_\_\_ hrs.  
Artesian flow \_\_\_\_\_ g.p.m.  
Temperature of water 50 Depth artesian flow encountered \_\_\_\_\_ ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT CROUT  
Well sealed from land surface to 35 ft.  
Diameter of well bore to bottom of seal 12 in.  
Diameter of well bore below seal 8 in.  
Number of sacks of cement used in well seal 7 sacks  
Number of sacks of bentonite used in well seal \_\_\_\_\_ sacks  
Brand name of bentonite \_\_\_\_\_  
Number of pounds of bentonite per 100 gallons of water \_\_\_\_\_ lbs./100 gals.  
Was a drive shoe used?  Yes  No Plug \_\_\_\_\_ Size: location \_\_\_\_\_ ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? \_\_\_\_\_ depth of strata \_\_\_\_\_  
Method of sealing strata off \_\_\_\_\_  
Was well gravel packed?  Yes  No Size of gravel: 4  
Gravel placed from 61 ft. to 110 ft.

(10) LOCATION OF WELL:

County CLATSOP Driller's well number \_\_\_\_\_  
NE 1/4 SW 1/4 Section 32 T. 25 R. 7E W.M.  
Bearing and distance from section or subdivision corner \_\_\_\_\_

(11) WATER LEVEL: Completed well.

Depth at which water was first found 15 ft.  
Static level 22 ft. below land surface. Date 10/26/73  
Artesian pressure \_\_\_\_\_ lbs. per square inch. Date \_\_\_\_\_

(12) WELL LOG:

Diameter of well below casing 8"  
Depth drilled 116 ft. Depth of completed well 110 ft.  
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	2	
RED SANDY CLAY & Boulders	2	8	
SAND STONE GRAY	8	26	11
GRAY SAND	26	38	
GRAY SAND & Boulders	38	116	22

Work started 8/2 1973 Completed 10/26 1973  
Date well drilling machine moved off of well 10/28 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] Wallace J. Daasland Date 11/11, 1973  
(Drilling Machine Operator)  
Drilling Machine Operator's License No. 380

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name CARPISLAND DRILLING CO  
(Person, firm or corporation) (Type or print)  
Address Box 31 Eagle Creek Ore  
[Signed] Wallace J. Daasland  
(Water Well Contractor)  
Contractor's License No. 543 Date 11/11, 1973