NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

LAN 10 1972 TATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date STATE ENGINEER within 30 days from the date STATE ENGINEER PROPERTY.	or print) ove this line) O768 State Permit N	· · · · · · · · · · · · · · · · · · ·	
of well completion. SALEM. OF One write ab	Sec decker inc		
(1) OWNED.	(10) LOCATION OF WELL:		
(1) OWNER:	County Clackanas Driller's well number		
Name River Bliff Park Co. Address Hoodland Park Plaza Wemme, Ore. 97067		- C	
Address Goods and Park Plaza Wenne, Ore, 4/00/	34 34 Section 33 T. 2-5		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner	
New Well Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 40 ft.		
Rotary Driven Domestic Domestic Municipal Domestic Municipal Domestic	Static level 35 ft. below land s	surface, Date 12-23-71	
Dug □ Bored □ Irrigation □ Test Well □ Other □	Artesian pressure lbs. per squar	re inch. Date	
CASING INSTALLED: Threaded Welded wall 8 " Diam. from 0 ft. to 85 ft. Gage wall "Diam. from ft. to ft. Gage		below casing 8. leted well 95 open ft. and structure of materials;	
" Diam. from	and show thickness and nature of each stratum with at least one entry for each change of forma	tion. Report each change in	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	T	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Sandy clay and boulders	0 10	
perforations from ft. toft_	_Big Boulders	10 15	
perforations from ft. to ft.	Dandy clay and boulders	15 35	
perforations fromft. toft.	- Big Boulders	35 45	
(7) SCREENS: Well screen installed? Yes No	-Gray glacerial rock	45 100	
Manufacturer's Name	, va-		
Type Model No			
Diam. Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
" " "	21		
Rich test 80 gal./min. with 40 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.	7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7		
Emperature of water Depth artesian flow encounteredft.	Work started to to the 10 Complet		
iperature of water Depth artesian now encountered	Work started 12-12-71 19 Complet		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	12-23-71 19	
Well seal-Material used Bentonite	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	above are true to my	
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Date 1-5-72, 19 (Drilling Machine Operator)		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	254	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's Intense No.		
Brand name of bentonite National	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons 50	This well was drilled under my jurisd	iction and this report is	
of waterlbs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Pigs Size: location ft.	Name Ralph Jurner Drilling Co.		
Did any strata contain unusable water: Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rie I Box 141 Hillsboro, Oregon		
Method of sealing strata off	[Signed] And International	74,	
Was well gravel packed? Yes No Size of gravel:	Contractor's License No. 247 Date	ractor) 1-5-72	
Gravel placed fromft. toft.	Contractor's License No Date		