The original and first	
STATE ENGINEER, SALEMOPEGO 2732 NOINEER Please type within 30 days from the date of well completion. SALEM OF TO Open or write about	or print) Ove this line)
Stel	
(1) OWNER:	(10) LOCATION OF WELL:
Name River Bluff Park Co.	County Clackanas Driller's well number
Address Hoodland Park Plaza Weme, Oregon 97067	14 14 Section 33 T.2-5 R. 7-E W.M.
The second secon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) TYABED I EXTEL. Completed well
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Oriven Domestic Municipal Domestic Municipal Domestic	Static level ft. below land surface. Date
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded Welded Welded Gage Wall By Diam. from ft. to ft. Gage "Diam. from ft. to ft. Gage "Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing Depth drilled 102 ft. Depth of completed well q8 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	
perforations fromft. toft.	Drilled down to bentonite and resealed
perforations from	335555
· .	
perforations fromft. toft.	, and a second s
(7) SCREENS: Well screen installed? Yes No	
Manufacturer's Name	
Type Model No	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	A SUB-PROPERTY OF THE SUB-PROPERTY AND ADDRESS OF THE SUB-PROPERTY ADDRESS OF THE SUB-PROPERTY AND ADDRESS OF THE SUB-PROPERTY ADDRESS OF THE SUB-
" " "	The state of the s
" "	And the same of th
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
	WW. J. J. J. J. D. T. J. Comp. 10
Temperature of water Depth artesian flow encountered ft.	Work started μ-5-72 19 Completed μ-10-72 19
CONSTRUCTION:	Date well drilling machine moved off of well-10-72
Well seal-Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore to bottom of sealin.	
Diameter of well bore below seal in.	[Signed] Date 4-15-72 19 Date 4-15-72 19
Number of sacks of cement used in well seal	Drilling Machine Operator's License No254
Number of sacks of bentonite used in well seal	
Brand name of bentoniteNational	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons 50	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? Tyes Z No Plugs Size: location ft.	Name Ralph Jurner rilling Co. (Type or print)
Did any strata contain unusable water? Yes No	Section is an experience of the section of the sect
Type of water? depth of strata	Address Rte 1 Box 141 Hillsboro, Oregon
Method of sealing strata off	[Signed] Palak July 114
Was well gravel packed? ☐ Yes ※ No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 247 Date 4-15-72 19