NOTICE TO WATER WELL CONTRACTOR

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97319 within 30 days from the date of well completion.

CLAC

WATER WELL REPORT STATE OF OREGON

(Please type or print)

(Do not write above this line)

DAX-Tri	State V
1.4	State 1

(1) OWNER:	(10) LOCATION OF WELL:
Name Jacque E. Parsons	County Clackamas Driller's well number 2337
Address 25460 S.W.Baker Rd.	34 34 Section 4 T. 3S R. 1W W.M.
Sherwood, Oregon 97140	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🖟 Deepening 🗆 Reconditioning 🗀 Abando	n 🗋
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (chec	1 7 7
tary N Driven Domestic Industrial Munic	- 10/21/20
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: glued Threaded Welded W	(12) WELL LOG: Diameter of well below casing 6" to 244
8 "Diam from top ft. to 84 ft. Gage 225	Denth drilled 244 ft Denth of completed well 244 ft.
VC' Diam. from XXX 82 ft. to 140 ft. Gage 1601	PSI and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? Yes No	nocition of Static Water Level and indicate principal water-hearing strate
Type of perforator used XX Skilsaw	MATERIAL From To SWL
tre of perforations 1/8 in. by 8 in.	Topsoil 0 4
72 perforations from 120 ft. to 140	n. Gray Silty Clay, surface water 4 16 4
perforations fromft. to	10 00
_	60 75
perforations from ft. to	Black Basalt 75 89
(7) SCREENS: Well screen installed? ☐ Yes 🖔 No	Brown Lava (20 gpm) 89 101 76
Manufacturer's Name	Black Basalt 101 163
TypeModel No.	
Diam. Slot size Set from ft. to	
Diam. Slot size Set from ft. to	
	D1 1 D 1+
(8) WELL TESTS: Drawdown is amount water level lowered below static level	Black Broken Basalt, water 236 241
a pump test made? ☐ Yes ☑ No II yes, by whom?	Black Basalt 241 244
	DEOFILE
Yield: gal./min. with ft. drawdown after	hrs.
40 GPM with rod at 120 for a period of 2	NOV 31980
<i>"</i> " " " " " " " " " " " " " " " " " "	3. 3.000
er test gal./min. with ft. drawdown after	hrs. WATER RESOURCES DEPT
Artesian flow g.p.m.	SALEM, OREGON
Temperature of water Depth artesian flow encountered	1011 100 1010100
(A) CONCERNICATION	Date well drilling machine moved off of well 10/21/80 19
(9) CONSTRUCTION: Cement	
Wall seal-Material used Portland KWHWK & 5% ben	This well was constructed under my direct supervision.
Well sealed from land surface to 84	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 8" to 140fth 6" to 24	best knowledge and belief [Signed] Dellas C. Green Date 10/21/8019 (Drilling Machine Operator)
Number of sacks of cement used in well seal	(Drilling Machine Operator)
How was cement grout placed? pumped in thru conduct	tor piprilling Machine Operator's License No
	Water Well Contractor's Certification:
And the second s	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugg Size: location	Willemette Drilling Co
Did any strata contain unusable water? Tres No	Name Willamette Drilling Co. (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 7365 O'Neil Rd. N.E. Salem, Oregn 9730
Method of sealing strata off	[Signed] Dallas Lagers
Was well gravel packed? [Yes VNo Size of gravel:	(Water Well Contractor)
Gravel placed from ft to ft.	Contractor's License No. 561 Date 10/21/80 19