

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

RECEIVED

35/1W-4ca

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)

MAR 9 1978

State Well No.

State Permit No.

CLAC
17744

(1) OWNER:

Name Jack Parsons
Address 25460 S.W. Baker
Sherwood, Oregon 97140

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

8" Diam. from +2 ft. to 97 ft. Gage .250
Threaded Welded

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? Driller
Yield: 60+ gal./min. with ft. drawdown after 1 1/2 hrs.
Air Rotary " Total " "
" " " "
" " " "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout
Well sealed from land surface to 98 ft.
Diameter of well bore to bottom of seal 8 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 24 sacks
How was cement grout placed?

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number D-96-78
NE 1/4 SW 1/4 Section 4 T. 3S R. 1W W.M.
Bearing and distance from section or subdivision corner

Sherwood Area

(11) WATER LEVEL: Completed well.

Depth at which water was first found 32 ft.
Static level 25 ft. below land surface. Date 2-23-78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"

Depth drilled 155 ft. Depth of completed well 155 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Clay Brown Med	2	26	
Bldrs broken med layered clay brn med	26	40	
Sandstone med frct	40	88	
Basalt hard gray	88	143	
Decomposed rock	143	154	
Basalt gray hard	154	155	

Work started 2- 20 1978 Completed 2 - 23 1978

Date well drilling machine moved off of well 2 - 23 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Jay Bane Date 3- 6, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1038

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name S & M Drilling & Supply, Inc
(Person, firm or corporation) (Type or print)
Address 399 S.E. Walnut/ Canby, Or 97013

[Signed] [Signature] (Water Well Contractor)

Contractor's License No. 497 Date 3- 6, 1978