STATE OF OREGON	CLAC	78034	WELL I.D. LABEL#	
WATER SUPPLY WELL REPORT			START CARD #	222014
(as required by ORS 537.545 & 537.765 and OAR 690-205-0210)	6/23/	2023	ORIGINAL LOG#	
(1) LAND OWNER Owner Well I.D.				*
First Name DANIEL Last Name WEHRMAN	•	(N) LOCA	TION OF WELL (logal	desamintion)
Company			TION OF WELL (legal	
Address 23737 SW NEWLANDE ROAD				N/S Range 1.00 E E/W WN
City WILSONVILLE State OR 7 in 97070		Sec <u>31</u>	SE 1/4 of the SE	_ 1/4 Tax Lot <u>1700</u>
City WILSONVILLE State OR Zip 97070 (2) TYPE OF WORK New Well Deepening Conv	version	Tax Map Num	ıber	Lot
Alteration (complete 2a & 10) Abandonment(co		Lat	nber" or 45.3485000 	DMS or DD
(2a) PRE-ALTERATION	ompiete 5a)	Long	" or -122.72386	DMS or DD
Dia + From To Gauge Stl Plstc Wld Thrd		(e) S	Street address of well N	earest address
Casing:		23737 SW N	EWLANDE ROAD, WILSONV	VILLE, OR 97070
Material From To Amt sacks/lbs				
Seal:				
(3) DRILL METHOD		(10) STAT	IC WATER LEVEL	
Rotary Air Rotary Mud Cable Auger Cable Mud		h	Dat	te SWL(psi) + SWL(ft)
Reverse Rotary X Other NONE USED		Complete	Well / Pre-Alteration	
		Complete	Flowing Artesian?	Dry Hole?
(4) PROPOSED USE Domestic Irrigation Community				- 🗀
Industrial/ Commericial Livestock Dewatering		WATER BEAL	RING ZONES Depth w	vater was first found
Thermal Injection Other	_	SWL Date	From To Es	st Flow SWL(psi) + SWL(ft)
(5) BORE HOLE CONSTRUCTION Special Standard X (A	Attach conv)			
Depth of Completed Well ft.	Attach copy)	l 	+ + +	
BORE HOLE SEAL	sacks/	l 	+ + +	
	Amt lbs			
Calculated				
		(11) XVELT	LOC	
Calculated		(11) WELL	Ground Elevation	on
How was seal placed: Method A B C D	E		Material	From To
Other				
Backfill placed from ft. to ft. Material				
Filter pack from ft. to ft. Material Size				
Explosives used: Yes Type Amount				
(5a) ABANDONMENT USING UNHYDRATED BENTONI		<u> </u>		
Proposed Amount 96.00 Sacks Actual Amount 106.00 Sack	S			
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc				
Casing Liner Dia + From To Gauge Stl Plstc	Wld Thrd			
	HH			
	HH			
	H			
	шш			
Shoe Inside Outside Other Location of shoe(s)		 		
Temp casing Yes Dia From + To				
(7) PERFORATIONS/SCREENS		<u> </u>		
Perforations Method				
Screens Type Material		Date Starte	d6/20/2023 Con	npleted <u>6/21/2023</u>
Perf/ Casing/ Screen Scrn/slot Slot # of		(lll)	900 March 1907 Parker 1909	-
Screen Liner Dia From To width length slots	pipe size		Water Well Constructor Certif	ncation construction, deepening, alteration, or
				construction, deepening, alteration, of ce with Oregon water supply well
		construction	standards Materials used and i	nformation reported above are true to
			y knowledge and belief.	mornation reported above are true to
		0.7		Date
(O) WIELL TECTO M:		License i tuin		
(8) WELL TESTS: Minimum testing time is 1 hour		Signed		
Pump Bailer Air Flowing A	rtesian			
Yield gal/min Drawdown Drill stem/Pump depth Duration (l	hr)	(bonded) Wa	ter Well Constructor Certifica	ition
				deepening, alteration, or abandonmen
				ruction dates reported above. All wor
				nce with Oregon water supply we
Temperature °F Lab analysis Yes By				the best of my knowledge and belief.
Water quality concerns? Yes (describe below) TDS amount 46.3 From To Description Amount	ppm	License Num	ber 1273 D	Date 6/23/2023
From To Description Amount	Units			
	 			
	 	Contact Info (optional)	
		<u> </u>		

Amended 7/22/2023

(8) WELL TESTS: Minimum testing time is 1 hour

Drill stem/Pump depth

Duration (hr)

Drawdown

Yield gal/min

											Page 2	2 of
	78034		W		I.D. LA							
				S	TART C	ARD#	222	014			Page 2 of the Units + SWL(ft)	
/	2023			OR	IGINAL	LOG#						
	Water Qu	ualit	y Con	cern	ıs							
	From	To)		Desc	ription		1	Amou	ınt	Units	
_												
(10) STA											
	SWL Date	e	From	1	То	Est F	low	SWL	(psi)	+	SWL(ft)	7
									-	Н		+
												1
												1
										Н		1
]
										Н		-
												1

(11) WELL LOG

Material	From	To

Comments/Remarks

This 6-inch well was 320 ft. with a static water level of 294 feet. The well was abandoned using bentonite, screened and poured from 320 ft to 4 ft. The casing was cut off 4 inches below a concrete slab. A cement cap was placed from 4 ft to flush with the concrete floor. 106 bags of bentonite & 1 sack cement were used to abandon this well. Original well log was not located for this well. Abandonment done with Special Standards were approved by Tommy Laird of WRD.

CLAC 78034

6/23/2023

Map of Hole

STATE OF OREGON WELL LOCATION MAP

This map is supplemental to the WATER SUPPLY WELL REPORT

Oregon Water Resources Department

725 Summer St NE, Salem OR 97301 (503)986-0900



LOCATION OF WELL

Latitude: 45.34850000 Datum: WGS84

Longitude: -122.72386800

Township/Range/Section/Quarter-Quarter Section:

WM2.00S1.00E31SESE

Address of Well:

23737 SW NEWLANDE ROAD, WILSONVILLE, OR 97070

Startcard: 222014

Printed: June 23, 2023

DISCLAIMER: This map is intended to represent the approximate location the well. It is not intended to be construed as survey accurate in any manner.

Provided by well constructor

