

STATE OF OREGON  
WATER SUPPLY WELL REPORT

CLAC 78804

WELL I.D. LABEL# L

151671

START CARD #

1073989

ORIGINAL LOG #

(as required by ORS 537.545 &amp; 537.765 and OAR 690-205-0210)

9/6/2024

## (1) LAND OWNER

Owner Well I.D. \_\_\_\_\_

First Name \_\_\_\_\_ Last Name \_\_\_\_\_

Company WHISKEY HILL PLANTS

Address PO BOX 1201

City CANBY State OR Zip 97013

## (2) TYPE OF WORK

☒ New Well ☐ Deepening ☐ Conversion☐ Alteration (complete 2a & 10) ☐ Abandonment (complete 5a)

## (2a) PRE-ALTERATION

Casing: Dia + From To Gauge Stl Plstc Wld Thrd  
Material From To Amt sacks/lbs  
Seal: \_\_\_\_\_

## (3) DRILL METHOD

☒ Rotary Air ☐ Rotary Mud ☒ Cable ☐ Auger ☐ Cable Mud  
☐ Reverse Rotary ☐ Other \_\_\_\_\_

## (4) PROPOSED USE

☐ Domestic ☒ Irrigation ☐ Community  
☐ Industrial/ Commercial ☐ Livestock ☐ Dewatering  
☐ Thermal ☐ Injection ☐ Other \_\_\_\_\_

## (5) BORE HOLE CONSTRUCTION

Special Standard ☐ (Attach copy)

Depth of Completed Well 449.00 ft.

BORE HOLE			SEAL				sacks/
Dia	From	To	Material	From	To	Amt	lbs
12	0	65	Bentonite	0	5	5	S
8	65	457			Calculated	3.5	
			Cement	5	65	28	S
					Calculated	21	

Seal placement method ☐ A ☐ B ☒ C ☐ D ☐ E ☒ Other: BENT DRY & HYDRATE

Backfill placed from 449 ft. to 457 ft. Material GRAVEL

Filter pack from 348 ft. to 449 ft. Material CSS Size 8/12

Explosives used: ☐ Type \_\_\_\_\_ Amount \_\_\_\_\_

Seal Placement Begin Date 8/20/2024 Begin Time 11 15

## (5a) ABANDONMENT USING UNHYDRATED BENTONITE

Proposed Amount

Actual Amount

## (6) CASING/LINER

C/L	Dia	+ From To Gauge	Mat. Type	Wld	Thrd	Shoe	Shoe Location
C	8	<input checked="" type="checkbox"/> 2 388 0.250	ST	<input checked="" type="checkbox"/>		OUT.	457
L	6	<input type="checkbox"/> 346 367 0.250	ST	<input checked="" type="checkbox"/>			
L	5	<input type="checkbox"/> 367 388 0.250	ST	<input checked="" type="checkbox"/>			
L	5	<input type="checkbox"/> 428 449 .258	ST	<input checked="" type="checkbox"/>			

Temp casing ☒ Yes Dia 12 From + ☒ 1 To 60.8

## (7) PERFORATIONS/SCREENS

Perforations Method \_\_\_\_\_

Screens Type V-Wire Material Stainless Steel

Perf/ Screen	Casing/ Liner	Screen Dia	From	To	Scrn/slot width	Slot length	# of slots	Tele/ Pipe size
S		5"	388	428	.060			Pipe

## (8) WELL TESTS: Minimum testing time is 1 hour

Type of Test	Yield (gal/min)	Drawdown	Drill Stem/ Pump Depth	Duration (hr)
Pump	250	179	336	4

Temperature 56 °F Lab analysis ☐ Yes By \_\_\_\_\_Water quality concerns? ☐ Yes (describe below) TDS amount 116 ppm

From	To	Description	Amount	Units

## (9) LOCATION OF WELL (legal description)

County CLACKAMAS Twp 5.00 S N/S Range 1.00 W E/W WM

Sec 1 NE 1/4 of the SW 1/4 Tax Lot 2201

Tax Map Number \_\_\_\_\_ Lot \_\_\_\_\_

Lat \_\_\_\_\_ " or 45.16354000 DMS or DD

Long \_\_\_\_\_ " or -122.75744000 DMS or DD

☒ Street address of well ☐ Nearest address

30711 S MERIDIAN RD, HUBBARD, OR

## (10) STATIC WATER LEVEL

	Date	SWL (psi)	+	SWL (ft)
Existing Well / Pre-Alteration				
Completed Well	8/21/2024			74.7
Flowing Artesian?	<input type="checkbox"/>			
Dry Hole?	<input type="checkbox"/>			

## WATER BEARING ZONES

Depth water was first found 135.00

SWL Date	From	To	Est Flow	SWL (psi)	+	SWL (ft)
6/12/2024	135	153	75			99.7
6/12/2024	164	168	20		<input checked="" type="checkbox"/>	
6/14/2024	229	232	30		<input checked="" type="checkbox"/>	

## (11) WELL LOG

Ground Elevation \_\_\_\_\_

Material	From	To
SOIL	0	2
CLAY BROWN MEDIUM	2	24
CLAY BROWN WITH GRAVELS	24	40
CLAY BROWN MEDIUM	40	60
CLAY BROWN WITH SAND LAYERS BROWN	60	80
SAND BROWN	80	86
SILT BROWN	86	94
CLAY GREY	94	97
CLAY GREY MEDIUM	97	102
SAND GREY WITH SOME GRAVELS DIRTY	102	107
SILT GREY	107	127
SAND GREY	127	135
SAND & GRAVEL GREY LOOSE	135	153
CLAYSTONE GREEN & GREY	153	162
CLAYSTONE GREEN & BROWN	162	164
CLAY WITH SAND LENSES	164	168
PACKED SILT GREY	168	173
CLAY GREY STICKY	173	180
CLAY GREEN MEDIUM	180	190

Construction

Begin Date 6/10/2024 Begin Time 00 00 End Date 8/21/2024

## (unbonded) Water Well Constructor Certification

I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief.

License Number \_\_\_\_\_ Date \_\_\_\_\_

Signed \_\_\_\_\_

## (bonded) Water Well Constructor Certification

I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.

License Number 688 Date 9/6/2024

Signed STEVEN STADELI (E-filed)

Drilling Company: WESTERBERG DRILLING INC

ORIGINAL - WATER RESOURCES DEPARTMENT

THIS REPORT MUST BE SUBMITTED TO THE WATER RESOURCES DEPARTMENT WITHIN 30 DAYS OF COMPLETION OF WORK Form Version:

New exempt use wells must be submitted with a map and recording fee.

**WATER SUPPLY WELL REPORT -**  
**continuation page**

CLAC 78804

WELL I.D. LABEL# L 151671

START CARD # 1073989

9/6/2024

ORIGINAL LOG #

**(2a) PRE-ALTERATION**

Dia	+	From	To	Gauge	Stl	Plstc	Wld	Thrd

Material	From	To	Amt	sacks/lbs

**(5) BORE HOLE CONSTRUCTION**

BORE HOLE				SEAL				sacks/ lbs
Dia	From	To	Material	From	To	Amt		
						Calculated		
						Calculated		
						Calculated		
						Calculated		
						Calculated		

**FILTER PACK**  
 From To Material Size


**(6) CASING/LINER**

C/L	Dia	+	From	To	Gauge	Mat. Type	Wld	Thrd	Shoe	Shoe Location

**(7) PERFORATIONS/SCREENS**

Perf/ Screen	Casing/ Liner	Screen Dia	From	To	Scrm/slot width	Slot length	# of slots	Tele/ Pipe size

**(8) WELL TESTS: Minimum testing time is 1 hour**

Type of Test	Yield (gal/min)	Drawdown	Drill Stem/ Pump Depth	Duration (hr)

**Water Quality Concerns**

From	To	Description	Amount	Units

**(10) STATIC WATER LEVEL**

SWL Date	From	To	Est Flow	SWL(psi)	+	SWL(ft)

**(11) WELL LOG**

Material	From	To
CLAY GREY STICKY	190	204
PACKED SILT HARD	204	218
SILT GREY	218	225
SILT WITH SAND GREY	225	229
PACKED SAND WITH GRAVEL	229	232
CLYSTONE GREY & GREEN	232	248
CLAY BROWN WITH SAND	248	252
CLAY GREY BLUE	252	255
PACKED SAND WITH CLAY BLUE	255	258
CLAY BLUE STICKY	258	265
CLAY WITH SILT & SAND	265	267
CLAY GREY STICKY	267	311
SILTY SAND GREY	311	314
CLAYSTONE GREEN	314	326
SAND GREY	326	330
CLAY GREEN	330	340
CLAY GREY STICKY	340	388
SILTSTONE GREY	388	390
SAND GREY	390	395
SILT GREY	395	398
SAND GREY	398	408
SILT LAVENDER	408	412
SAND GREY	412	427
CLAY GREY	427	457

Name of person(s) who assisted with construction and Trainee License # / Helper #

Assistant Name

Type

#

**Comments/Remarks**

8" DRIVE SHOE CUT OFF @ 457' SWL @ 135-153 NOT ACCURATE  
 DUE TO PUMPING WELL NEARBY  
 5 by 6 WELD ON BUSHINGS @ 367'  
 6" FLUSH DRIVE SHOE ON TOP OF 6" RISER PIPE  
 THIS WELL IS FOR WATER RIGHT TRANSFER T-14258

WATER SUPPLY WELL REPORT - Map with location identified must be attached and shall include an approximate scale and north arrow

CLAC 78804

9/6/2024

## Map of Hole

### STATE OF OREGON WELL LOCATION MAP

This map is supplemental to the WATER SUPPLY WELL REPORT

### Oregon Water Resources Department

725 Summer St NE, Salem OR 97301  
(503)986-0900



#### LOCATION OF WELL

Latitude: 45.16354000 Datum: WGS84

Longitude: -122.75744000

Township/Range/Section/Quarter-Quarter Section:

WM5.00S1.00W1NESW

Address of Well:

30711 S MERIDIAN RD, HUBBARD, OR

Well Label: 151671

Printed: September 6, 2024

DISCLAIMER: This map is intended to represent the approximate location the well. It is not intended to be construed as survey accurate in any manner.

Provided by well constructor

