NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. OS543 (Please type not write all	OREGON NOV 1 3 19/3 State Well No.			-25
(1) OWNER:	(10) LOCATION OF WELL:			
Name Paul Brown	County Clackamas Driller's well number			
Address Rte 2 Box 268A Aurora, Oregon	% % Section 25 T. 35	R. 1W	,	W.M.
The same of the sa	Bearing and distance from section or subdivis			VV.111.
(2) TYPE OF WORK (check):	- The state of the			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 61 ft.			
Rotary Driven Domestic Condustrial Confusional M	Static level 12 ft. below land surface. Date 10/26/7			
Cable	20 200 Mile Surface. Butc 10/20/1.			
	Artesian pressure Ibs. per squa	re inch.	Date	
(5) CASING INSTALLED: Threaded □ Welded □ 12" Diam. from □ ft. to □ 120 ft. Gage 14" □ 12" Diam. from □ ft. to □ ft. Gage □ 14" □ 14 □ 15 □ 15 □ 15 □ 15 □ 15 □ 15 □ 15	(12) WELL LOG: Diameter of well below casing Depth drilled 120 ft. Depth of completed well 120 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
(6) PERFORATIONS: Perforated? Wes No.	position of Static Water Level and indicate pri			
Type of perforator used Millknife	MATERIAL	From	То	swl
Size of perforations ½ in, by 4 in.	Surface	0	5	
	Brown clay	5	26	
perforations from ft. to ft.	Brown gravel	26	52	
perforations from ft. to ft.	Blue clay	52	61	<u> </u>
(7) SCREENS: Well screen installed? Yes X No	Black sand	61	72	
Manufacturer's Name	Black gravel	72	102	
Type Model No.	Blue clay	102	120	
Diam. Slot size Set from ft, to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static level	· · · · · · · · · · · · · · · · · · ·			
Was a pump test made? ☐ Yes ☐ No If yes, by whom? driller				
d: 300 gal/min, with 30 ft. drawdown after 24 hrs.				
William Control of the Control of th	:			
rnis well was pressure grouted				
from 80' to surface to comply	-			
with municipal requirements	Work started Oct O 1977 Complete			10
	Work started Oct 8 1973 Complet			1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Oct	29	1973
Well seal—Material used Cement Well sealed from land surface to 80 ft. Diameter of well bore to bottom of seal 18 in.	Drilling Machine Operator's Certification: This well was constructed under my Materials used and information reported best knowledge and belief.	direct	super are true	vision. to my
Diameter of well bore below seal12 in.		Date N	ov 2	, 19.7.3
Number of sacks of cement used in well seal sacks	Drilling Machine Operator) Drilling Machine Operator's License No.			•
Number of sacks of bentonite used in well seal sacks	Drimog Machine Operator's License No.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisd	iction an	d this re	eport is
water	LITTLE IN THE HEST OF MIX Enougledge and hel	inf		
Did any strata contain unusable water? Yes No	Name John Truman Miller (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address P 9 Box 341 Hubbard.	oregoi	pe or prin 1 07∩7) ろク
Method of sealing strata off	(1) 77 - 10	, 	×	d. 54
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] (Water Well Control		***************************************	
	· · // · /			
Gravel placed from ft. to ft.	Contractor's License No277 Date No.	v2		., 19.7.3