

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

RECEIVED

STATE OF OREGON (Please type or print)

RECEIVED

CLAG State Well No. 35/W-25

JAN 6 1978

(Do not write above this line)

FEB 17 1978

State Permit No. 08574

(1) OWNER:

Name Willamette Factors Address Wilsonville, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Driven [ ] Cable [ ] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [x] Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

Threaded [ ] Welded [x] 8" Diam. from 0 ft. to 4.33 ft. Gage .250

(6) PERFORATIONS:

Perforated? [ ] Yes [x] No

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [ ] Yes [x] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Baller test gal./min. with ft. drawdown after hrs. Artesian flow 60 g.p.m. Temperature of water 60 Depth artesian flow encountered 460 ft.

(9) CONSTRUCTION:

Well seal-Material used Cement Well sealed from land surface to 35 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 29 sacks Number of sacks of bentonite used in well seal Brand name of bentonite Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [x] Yes [ ] No Plug Size: location ft. Did any strata contain unusable water? [ ] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 1/4 Section 25 T. 3 R. 1 W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 55 ft. Static level ft. below land surface. Date Artesian pressure 2 lbs. per square inch. Date 11-29-77

(12) WELL LOG:

Diameter of well below casing 8 Depth drilled 541 ft. Depth of completed well 541 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Organic, Brown clay, Blue clay, Sand brown, Gravelly sand, Yellow brown clay, Blue clay, Brown sandsilty, Silty brown clay, Blue silt, Blue silty clay, Blue silt, Blue shale, Red shale, Brown basalt, Black basalt, Brown basalt, Black basalt, Pinhole lava black, Black basalt, Pinhole lava.

Test Pump will be mad by owner

Work started 11-16 797 Completed 11-29 1977 Date well drilling machine moved off of well 12-1 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Eugene Jordan Date 11-29, 1977 (Drilling Machine Operator)

Drilling Machine Operator's License No. 670 607

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Eugene Jordan (Person, firm or corporation) (Type or print)

Address 2126 First Ave E Canby, Oregon

[Signed] Eugene Jordan (Water Well Contractor)

Contractor's License No. 670 Date 11-29, 1977