NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED DEC 30 1983 WATER RESOURCES DEPT. SALEM, OREGON

CLAC 08584

State Well No. 3S/1W-26ab

State Permit No.

(1) OWNER:
Name Ed Miller
Address 26015 S.W. Boones Ferry
Wilsonville, Ore

(2) TYPE OF WORK (check):
New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):
Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED: Threaded [ ] Welded [X]
6" Diam. from +1 ft. to 89 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? [ ] Yes [X] No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? [X] Yes [ ] No
Manufacturer's Name Johnson
Type Stainless Steel Model No.
Diam. 5 5/8 Slot size 20 Set from 85 ft. to 115 ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? [ ] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 5 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 36' ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 25 sacks
How was cement grout placed? Poured Down Tremie Pipe
Was a drive shoe used? [X] Yes [ ] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Clackamas Driller's well number
NW ¼ NE ¼ Section 26 T. 3S R. 1W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 98 ft.
Static level 29 ft. below land surface. Date Nov 15
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 115 ft. Depth of completed well 115 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Overburden	0	1	
Light Brown Clay	1	53	
Gravel	53	60	
Blue Green Clay	60	98	
Sand & Gravel	98	115	29'

Work started Nov 1 1983 Completed Nov 18 1983
Date well drilling machine moved off of well Nov 22 1983

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Donald L. Crawell (Drilling Machine Operator) Date Dec 21, 1983
Drilling Machine Operator's License No. 1050

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Cris-Well Drilling Co. (Person, firm or corporation) (Type or print)
Address 610 S. Rosemont Rd. West Linn
[Signed] Donald L. Crawell (Water Well Contractor)
Contractor's License No. 647 Date Dec 21, 1983

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119